# Second Regular Session Seventy-first General Assembly STATE OF COLORADO

## REVISED

This Version Includes All Amendments Adopted on Second Reading in the Second House

LLS NO. 18-0534.01 Jery Payne x2157

**SENATE BILL 18-028** 

#### SENATE SPONSORSHIP

Scott,

## **HOUSE SPONSORSHIP**

Bridges,

#### **Senate Committees**

Transportation

#### **House Committees**

Transportation & Energy

## A BILL FOR AN ACT

101 CONCERNING THE REPEAL OF CERTAIN REQUIREMENTS FOR WHERE A 102 LICENSE PLATE IS MOUNTED ON A MOTOR VEHICLE.

# **Bill Summary**

(Note: This summary applies to this bill as introduced and does not reflect any amendments that may be subsequently adopted. If this bill passes third reading in the house of introduction, a bill summary that applies to the reengrossed version of this bill will be available at <a href="http://leg.colorado.gov">http://leg.colorado.gov</a>.)

Current law requires each license plate to be at the approximate center of a motor vehicle and at least 12 inches from the ground. The bill repeals this requirement for the front license plate.

1 Be it enacted by the General Assembly of the State of Colorado:

SENATE Amended 2nd Reading February 2, 2018

3rd Reading Unamended February 5, 2018

SENATE

Shading denotes HOUSE amendment.

Capital letters or bold & italic numbers indicate new material to be added to existing statute.

Dashes through the words indicate deletions from existing statute.

HOUSE d Reading Unamended March 12, 2018

1	SECTION 1. In Colorado Revised Statutes, 42-3-202, amend
2	(2)(a)(II) and (2)(a)(III) as follows:
3	42-3-202. Number plates furnished to be attached.
4	(2) (a) (II) Except when authorized by this article ARTICLE 3 or rule of the
5	department, each THE REAR license plate must be:
6	(A) Horizontal at a height not less than twelve inches from the
7	ground, measuring from the bottom of the plate;
8	(B) In a place and position to be clearly visible;
9	(C) Maintained free from foreign materials and clearly legible;
10	<del>and</del>
11	(D) At the approximate center of the vehicle measured
12	horizontally; AND
13	(E) MOUNTED ON OR WITHIN EIGHTEEN INCHES OF THE REAR
14	BUMPER.
15	(III) Except when authorized by this article or rule of the
16	department ARTICLE 3, the rear FRONT license plate must be: mounted on
17	or within eighteen inches of the rear bumper
18	(A) DISPLAYED HORIZONTALLY ON THE FRONT OF A MOTOR
19	VEHICLE IN THE LOCATION DESIGNATED BY THE MOTOR VEHICLE
20	MANUFACTURER;
21	(B) MAINTAINED FREE FROM FOREIGN MATERIALS; AND
22	(C) CLEARLY LEGIBLE.
23	SECTION 2. Safety clause. The general assembly hereby finds,
24	determines, and declares that this act is necessary for the immediate
25	preservation of the public peace, health, and safety.

-2- 028