# Caroma

# CI/SfB | (74.2) | g3 | Date | October 2015

Supersedes all previous issues

1.39.1

### **Liano Nexus 750**

**Ceramic Shelf Wall Basin** 

Nominal Size: 750mm x 450mm



Left hand shelf version shown

## Caroma

### Liano Nexus 750

#### **Ceramic Shelf Wall Basin**

Basin Size: 750mm x 450mm (nominal)

#### **Optional Ceramic Shroud**



Right hand shelf version pictured.

Tapware and shroud shown not included.

The **Liano Nexus 750** shelf wall basin is available with a right hand or left hand shelf, and is part of an extensive range of co-ordinated basins that allows continuity of design throughout the project where basins of matching design for different applications are required. The design offers clean lines incorporating a built in shelf space alleviating the need for separate shelving. Available with optional shroud, this basin is suitable for domestic, commercial and & accessible applications complying to AS 1428.1-2009 Amd. 1.\*

Tap Holes: Basin available in: Left Hand Shelf, no taphole Code No.665505; one taphole

Code No.665515. **Right Hand Shelf**, no taphole Code No.665405; one taphole

Code No.665415.

Waste Outlet: The basin has been designed for the Caroma waste outlet suitable for a 40mm

trap connection. Chrome flush fitting waste and white plug supplied. Alternative waste options are available — Plug & anti-vandal flush fitting chrome waste Code No.687141C; Plug & chrome grate waste Code No.687328C; Chrome pop-up

plug and waste Code No.687329C.

Shroud: Optional Liano Nexus Shroud, Code No.812270 completely conceals P-trap

waste pipe fittings, concealed fixing bracket supplied. 40mm Caroma short plastic P-trap is required for correct installation Code No.102115.

**Note:** It is essential for the installation of the shroud to the basin that clearance is provided for the shroud in the plumbing set out from water inlet pines and

is provided for the shroud in the plumbing setout from water inlet pipes and connections.

**Bowl Capacity:** 5.5 litres to overflow.

**Overflow:** Overflow available only. Designed for maximum tap flow rate of 15 litres/minute.

Fixing: D.200 Basin Fixing Kit – Supplied. Bolts directly to the finished wall.

Colours: White only.

**Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing

variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications

without notice.

\*Basin does not comply to NZS4121.

