

FEBRUARY 2025



ACRYFLASH

Product

Thermo baked acrylic primer coated lead flashing. One side Mid Grey the other Charcoal Grey. Either side up or customer can repaint to their own requirements.

Applications

For use as a flashing for both tile and metal roofs. Can also be used for roof penetrations. Note must be installed to Australian AS2904. Runs should not exceed 1.5 metres in length.

Form

Available in the following widths:

150mm
225mm
300mm
450mm
600mm
1220mm

In 3 or 6 metre Rolls

Also available in 450 & 600 squares

Thickness:

Available in 15kg (1.32mm) & 20kg (1.76mm)

Special sizes available on request

THIS DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION. CAGROUP PROVIDES NO WARRANTIES, EITHER EXPRESSED OR IMPLIED AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN. MATERIAL USE BEYOND THE CONTROL OF SUPPLIER

MELBOURNE (Head Office):
32 Industrial Avenue.
Thomastown, Vic. 3074
Telephone: (03) 8301 7100
Facsimile: (03) 9359 4076

SYDNEY:
5 Coates Place,
Wetherill Park, N.S.W. 2164
Telephone: (02) 8795 6300
Facsimile: (02) 9756 4074

BRISBANE:
62 Parramatta Road,
Underwood, Qld. 4119
Telephone: (07) 3086 7300
Facsimile: (07) 3209 3611

PERTH:
Unit 10, 305 Victoria Road
Malaga, W.A. 6090
Telephone: (08) 9207 9300
Facsimile: (08) 9248 9543