



Texas Safety Glasses Economy

PRODUCT DATA SHEET

ITEM CODE: EBR330e

Product Overview

- **Materials:** Polycarbonate
- **Lens Properties:** Anti-Scratch
- **Impact:** Medium impact
- **Category:** 0 (Clear), 3 (Smoke)
- **UV Rating:** UV380
- **Lens Markings:** I-0 (Clear) I-3 (Smoke)
- **Weight:** 22.4g
- **Country of Origin:** Taiwan

Cleaning and Maintenance

Storage: Safety glasses can be stored for 3 years from the manufacture date, the poly bag should be sealed and stored at temperature above 5°C and below 40°C. Keep away from solvents or any corrosive materials, as these may seriously reduce the impact protection provided by the spectacle.

Cleaning: Only use a dry wipe to clean as wet wipes will reduce the Anti-Fog function.

Warranty

Limited lifetime – manufacturing defects

Packaging

Pack: 12 pairs

Carton: 300 pairs

Accessories

| Product | Description |
|---------|------------------------------|
| CORD-BK | Black Spectacle Cord |
| ELT464 | Anti-Fog Lens Cleaning Wipes |
| EMB481 | Microfibre Glasses Case |



EBR330e - Clear



EBR331e - Smoke

Standards and Certification



AS/NZS 1337.1:2010
Lic. BMP 557823

| Colour | Reference | Features |
|-------------|-----------|---|
| Transparent | | Standard options providing the highest Visible Light Transmission (VLT) |
| Smoke | | Effectively dimming your surroundings and reducing excessive glare, and it is the most popular for outdoor applications |

Impact levels

| Eye & face protector type | low impact 12m/s | medium impact 45m/s | high impact 120m/s | extra high impact 190m/s |
|---------------------------|------------------|---------------------|--------------------|--------------------------|
| Wide vision spectacle | • | • | | |
| Goggle | • | • | | |
| Eye shield | • | • | | |
| Face shield | • | • | • | • |

| Type of protector | Ocular marking (s) (several may apply) | Eye protector marking (s) (several may apply) |
|------------------------------|---|--|
| Low impact | The letters 'HT' where the ocular is heat tempered The letters 'CT' where the ocular is chemically tempered Use of the letter 'S' is optional | No requirements additional to Clause 3.5.1a |
| Medium impact | 'I' or 'F'__* | 'I' or 'F'__* |
| High impact | 'V' or 'B'__* | 'V' or 'B'__* |
| Extra high impact | 'A' | 'A' |
| Molten metal and hot solids | 'M' or '9'__* | 'M' or '9'__* |
| Splashproof | | 'C' or '3'__* |
| Dustproof | | 'D' or '4'__* |
| Gaslight | | 'G' or '5'__* |
| Outdoor use, untinted | 'O' | 'O' |
| Sunglare ocular | Category number | |
| Photochromic sunglare ocular | Category numbers | |
| High temperature | 'H' | 'H' |

100% protection against dangerous UVA and UVB radiation

