



# Trail Boss Rigger

## PRODUCT DATA SHEET

ITEM CODE: GRP141

### Product Overview

- **Material:** Beige Cow Grain Leather, Polyester
- **Touch screen:** No
- **MSDS:** N/A
- **Food Contact:** No
- **Cuff Style:** Safety cuff
- **Country of Origin:** India



### Applications

- General purpose utility work glove
- Truck and transport industry
- Farm and agriculture applications
- Mining and construction industries
- Building industry
- Civil construction
- Rigging industry
- Timber and forestry
- Oil rigs and oil fields

### Care/Cleaning Instructions

You cannot wash the gloves as water wash is not appropriate for the leather, to clean use a soft brush.

### Packaging

Hangcard: 1 pair

Polybag: 6 pairs

Carton: 120 pairs

### Size Details

Product	Size	Hem Colour
GRP141-08	S	Green
GRP141-09	M	Brown
GRP141-10	L	Blue
GRP141-11	XL	Black
GRP141-12	2XL	Yellow

### Storage

The gloves are to be kept in an air-tight & climate-controlled conditions for a longer life.

### Warranty

Limited lifetime – manufacturing defects

### Standards and Certification




### Accessories

Code	Description
GGG115	Maxisafe Glove Clip

Glove and hand size chart as per standard EN ISO 21240

Glove size	5	6	7	8	9	10	11	12	13
Palm Circumferences	127mm	152mm	178mm	203mm	229mm	254mm	279mm	304mm	329mm
Hand Length	148mm	160mm	171mm	182mm	192mm	204mm	215mm	227mm	237mm
Standard Glove Sizes	XXS/5	XS/6	S/7	M/8	L/9	XL/10	XXL/11	3XL/12	4XL/13
Maxisafe Riggers and Mechanics Glove Sizes	XXS/6	XS/7	S/8	M/9	L/10	XL/11	XXL/12	3XL/13	4XL/14

AS/NZS 2161.3 Occupational protective gloves, Part 3:  
Protection against mechanical risk  
Based on EN388 – Protective gloves against mechanical risks.



EN388:2016  
XXXXXX

Abrasion	1-4
Cut (Coup Test)	1-5
Tear	1-4
Puncture	1-4
Cut (TDM Test ISO 13997)	A-F
Impact Protection	P,F,X

EN388:2016+A1:2018	Level 1	Level 2	Level 3	Level 4	Level 5
Abrasion resistance (number of cycles)	100	500	2000	8000	-
Blade cut resistance (index)	1.2	2.5	5	10	20
Tear resistance (N)	10	25	50	75	-
Puncture resistance (N)	20	60	100	150	-

EN ISO 13997:1999 TDM	Level A	Level B	Level C	Level D	Level E	Level F
Cut resistant test levels (N)	2	5	10	15	22	30

EN388:2016+A1:2018 IMPACT TEST	P (Pass)	F (Fail)	X
Average transmittance force (kg)	≤ 7kg	≥ 9kg	Not tested