

K-SPEC® HEAT SHRINK TUBING

CROSS-LINK POLYOLEFIN



100 Foot Rolls

- CSA Approved
- Flame Retardant (except Clear)
- Thin Wall 2:1 Ratio
- Oper. Temp.: -45°C to 125°C
- Shrink Temp.: Start at 70°C, recovery at 120°C
- Longitudinal shrink ratio: < or = 8%
- 600V rated

Tolerances

3/64"-1/4"	±.008"
5/16"-1/2"	±.012"
5/8"-3/4"	±.016"
5/16"-1/2"	±.012"
3/4"-1"	±.020"

C

Part No.	DESCRIPTION 100 FOOT SPOOLS	CTN/QTY
MHSP-3/64-0-C	HEAT SHRINK THIN-WALL BLACK 3/64"ID	100' SPL
MHSP-1/16-0-C	HEAT SHRINK THIN-WALL BLACK 1/16"ID	100' SPL
MHSP-3/32-0-C	HEAT SHRINK THIN-WALL BLACK 3/32"ID	100' SPL
MHSP-1/8-0-C	HEAT SHRINK THIN-WALL BLACK 1/8"ID	100' SPL
MHSP-1/4-0-C	HEAT SHRINK THIN-WALL BLACK 1/4"ID	100' SPL
MHSP-1/4-9-C	HEAT SHRINK THIN-WALL CLEAR 1/4"ID	100' SPL
MHSP-3/16-0-C	HEAT SHRINK THIN-WALL BLACK 3/16"ID	100' SPL
MHSP-3/8-0-C	HEAT SHRINK THIN-WALL BLACK 3/8"ID	100' SPL
MHSP-1/2-0-C	HEAT SHRINK THIN-WALL BLACK 1/2"ID	100' SPL
MHSP-1/2-9-C	HEAT SHRINK THIN-WALL BLACK 1/2"ID	100' SPL
MHSP-5/8-0-C	HEAT SHRINK THIN-WALL BLACK 5/8"ID	100' SPL
MHSP-5/8-9-C	HEAT SHRINK THIN-WALL BLACK 5/8"ID	100' SPL
MHSP-3/4-0-C	HEAT SHRINK THIN-WALL BLACK 3/4"ID	100' SPL