


## Butted Seam Barrel

## 12-10 WIRE RANGE

.040 Stock


Stamped out of the finest quality electrolytic copper, the terminal barrel is rolled and the seam is butted. Terminals employ the full barrel length that eliminates costly and time consuming location when crimping. Butted seam is the basic barrel style. Non-insulated and using a one-piece design, it is the most economical style and is ideal for the greatest variety of applications, where special features are not required.



Copper Stranded Wire Only

Terminals are NOT Actual Size See Sizing Chart on B-38, B-39

Stud Size	Part Number	Stud Size	Part Number
4-6	R1C6S	4-6	BS1C6
4-6	R1C6	8	BS1C8
6-8	R1C8S	10	BS1C10
6-8	R1C8		Parallel P1C
8-10	R1C10		Butt B1C
12-1/4	R1C14S		
1/4-5/16	R1C56S		
5/16-3/8	R1C38		
7/16-1/2	R1C12		

Part Number	W	L
B1C		0.560"
BS1C10	0.325"	0.772"
BS1C6	0.314"	0.731"
BS1C8	0.324"	0.767"
P1C		0.311"
R1C10	0.377"	0.772"
R1C12	0.760"	1.280"
R1C14S	0.530"	0.936"
R1C38	0.592"	1.040"
R1C56S	0.529"	0.936"
R1C6	0.377"	0.765"
R1C6S	0.283"	0.686"
R1C8	0.376"	0.716"
R1C8S	0.295"	0.686"



Add suffix "M" for 1000 pack  
Add suffix "P" for Pro Pack (Quantities vary by Part #)

Approved installation tool: See tool chart pages E-2,3,4  
Economy installation tools: RAT-NINS, 453, HTS1000  
See pages E-2 to E-4 for installation tools.

B