


K-SPEC® CABLE TIES

Wing Push Mount Cable Ties

- Material with Pure Nylon 6.6, UL 94V-2, Operation temp. -40°C~+85°C (-40°F ~+185°F)




RoHS PAHs Reach



A



Part no.	Colour	Width mm [Inch]	Length mm [Inch]	Max Bundle Diameter mm [inch]	Min Loop Tensile Kgs [lb]	Std. Pk. Qty.
E750WPM0C	Black	4.8 [.189]	200 [8.0]	49.6 [1.96]	22 [50]	100
E750WPM9C	Natural					

Part no.	Colour	W1 mm [inch]	W2 mm [inch]	D1 mm [inch]	H (max Panel Thickness) mm [inch]	Min Hole Size mm [inch]
E750WPM0C	Black	7.60 [.299]	17.8 [.700]	4.50 [.177]	2.50 [.098]	5.90 [.232]
E750WPM9C	Natural					



K-SPEC® SCREW MOUNTS

- Secure Support** deep cradle design provides maximum support for larger bundles and tubing
- Easy Insertion of Cable Ties** deep recessed screw hole allows cable ties to pass over screw head



Standard Screw Mounts Natural & UV Black

- Material with Pure Nylon 6.6, UL 94V-2, Operation temp. -40°C~+85°C (-40°F ~+185°F)

Part no.	Colour	(L) Length mm [Inch]	(W) Width mm [Inch]	(H) Height mm [Inch]	(D) Diameter mm [inch]	For Cable Ties width up to mm [inch]	Std. Pk. Qty.
KSNY0010C	Black	15.2 [.600]	9.4 [.370]	6.80 [.267]	3.30 [.130]	4.8 [.189]	100
KSNY0019C	Natural						
KSNY0010D	Black	15.2 [.600]	9.4 [.370]	6.80 [.267]	3.30 [.130]	4.8 [.189]	500
KSNY0019D	Natural						
KSNY0030C	Black	17.8 [.700]	12.7 [.500]	8.20 [.320]	4.31 [.170]	4.8 [.189]	100
KSNY0039C	Natural						
KSNY0030D	Black	17.8 [.700]	12.7 [.500]	8.20 [.320]	4.31 [.170]	4.8 [.189]	500
KSNY0039D	Natural						
KSNY0020C	Black	22.0 [.870]	16.2 [.640]	9.60 [.385]	5.20 [.205]	7.6 [.300]	100
KSNY0029C	Natural						
KSNY0020D	Black	22.0 [.870]	16.2 [.640]	9.60 [.385]	5.20 [.205]	7.6 [.300]	500
KSNY0029D	Natural						
KSNY0040C	Black	25.4 [1.00]	16.2 [.640]	10.80 [.425]	5.20 [.205]	9.0 [.354]	100
KSNY0049C	Natural						
KSNY0040D	Black	25.4 [1.00]	16.2 [.640]	10.80 [.425]	5.20 [.205]	9.0 [.354]	500
KSNY0049D	Natural						



NEW

NEW

NEW

NEW

NEW

NEW

NEW

NEW

Tolerance: ±.03"/.76 mm