


K-SPEC® CABLE TIES


Push Mount Cable Ties

- Material with Pure Nylon 6.6, UL 94V-2,
Operation temp. -40°C~+85°C (-40°F ~+185°F)


RoHS PAHs Reach


Part no.	Colour	Width mm [Inch]	Length mm [Inch]	Max Bundle Diameter mm [inch]	Min Loop Tensile Kgs [lb]	Std. Pk. Qty.
E750PM0C	Black	4.8 [.189]	200 [8.0]	50.8 [2.00]	22 [50]	100
E750PM9C	Natural					

Part no.	Colour	W1 mm [inch]	D1 mm [inch]	H (max Panel Thickness) mm [inch]	Min Hole Size mm [inch]
E750PM0C	Black	7.00 [.275]	4.30 [.169]	3.90 [.153]	4.90 [.193]
E750PM9C	Natural				



Releasable Cable Ties (Trigger type)

- Material with Pure Nylon 6.6, UL 94V-2,
Operation temp. -40°C~+85°C (-40°F ~+185°F)


RoHS PAHs Reach


Part no.	Colour	Width mm [Inch]	Length mm [Inch]	Max Bundle Diameter mm [inch]	Min Loop Tensile Kgs [lb]	Std. Pk. Qty.
E550R0C	Black	7.6 [.300]	150 [6.0]	40.3 [1.59]	22 [50]	100
E550R9C	Natural					
E850R0C	Black	7.6 [.300]	200 [8.0]	55.6 [2.19]	22 [50]	100
E850R9C	Natural					
E1450R0C	Black	7.6 [.300]	370 [14.5]	109.9 [4.33]	22 [50]	100
E1450R9C	Natural					