


ALUMINIUM TWO BARREL CONNECTORS – TWO HOLE MOUNT

- Made of high strength aluminium - 6061-T6
- Used for copper and or aluminium conductors.
- Electro - Tin plated for low contact resistance and protection against corrosion.
- Connectors are re-usable.
- cULus 486B listed
- Rated 600 volts / 90°C




PART NO	CONDUCTOR RANGE		STUD HOLE	DIMENSION IN INCHES					
	MIN	MAX		L	W	F	D	A	FIG NO
L2A3502	6 STR	350 KCMIL	1/2	4.12	1.91	0.31	0.62	1.75	1
L2A6002	4 STR	600 MCM	1/2	5.58	2.40	0.44	0.62	1.75	2
L2A8002*	350 KCMIL	800 MCM	1/2	5.82	3.19	0.50	0.62	1.75	2

* Not UL Listed

ALUMINIUM THREE BARREL CONNECTORS – TWO HOLE MOUNT

- Made of high strength aluminium - 6061-T6
- Used for copper and or aluminium conductors.
- Electro - Tin plated for low contact resistance and protection against corrosion.
- Connectors are re-usable.
- cULus 486B listed
- Rated 600 volts / 90°C



PART NO	CONDUCTOR RANGE		STUD HOLE	DIMENSION IN INCHES					
	MIN	MAX		L	W	F	D	A	FIG NO
L3A2502	6 STR	250 MCM	1/2	4.12	2.83	0.31	0.62	1.75	1
L3A3502	6 STR	350 MCM	1/2	4.12	3.00	0.31	0.62	1.75	1
L3A6002	2 STR	600 MCM	1/2	5.58	3.75	0.44	0.62	1.75	2
L3A8002*	300 MCM	800 MCM	1/2	5.82	4.50	0.50	0.62	1.75	2
L3A10002*	500 MCM	1000 MCM	1/2	5.82	4.54	0.50	0.62	1.75	2

* Not UL Listed

ALUMINIUM THREE BARREL CONNECTORS – FOUR HOLE MOUNT

- Made of high strength aluminium - 6061-T6
- Used for copper and or aluminium conductors.
- Electro - Tin plated for low contact resistance and protection against corrosion.
- Connectors are re-usable.
- cULus 486B listed
- Rated 600 volts / 90°C




FIG. 1

FIG. 2

PART NO	CONDUCTOR RANGE		STUD HOLE	DIMENSION IN INCHES					
	MIN	MAX		L	W	F	D	A	FIG NO
L3A2504	6 STR	250 KCMIL	1/2	4.12	2.83	0.31	0.62	1.75	1
L3A3504	6 STR	350 KCMIL	1/2	4.12	3	0.31	0.62	1.75	1
L3A6004	2 STR	600 MCM	1/2	5.58	3.75	0.44	0.62	1.75	2
L3A8004*	350 KCMIL	800 MCM	1/2	5.82	4.5	0.5	0.62	1.75	2
L3A10004*	500 KCMIL	1000 MCM	1/2	5.85	4.55	0.5	0.62	1.75	2

* Not UL Listed