


## Butted Seam Barrel

## 22-18 WIRE RANGE















.032 Stock

Stamped out of the finest quality electrolytic copper, the terminal barrel is rolled and the seam is butted. Terminals employ the full barrel length that eliminates costly and time consuming location when crimping. Non-insulated and using a one-piece design, it is the most economical style and is ideal for the greatest variety of applications, where special features are not required.



**Copper Solid and Stranded Wire Only**



Stud Size	Part Number	Stud Size	Part Number
4-6	 <b>R1A6S</b>	10	 <b>BS1A10</b>
4-6	 <b>R1A6</b>		 Parallel <b>P1A</b>
6-8	 <b>R1A8</b>		 Butt <b>B1A</b>
8-10	 <b>R1A10</b>		 <p><b>Terminals are NOT Actual Size See Sizing Chart on B-38, B-39</b></p>
12-1/4	 <b>R1A14S</b>		
1/4-5/16	 <b>R1A56S</b>		
5/16-3/8	 <b>R1A38</b>		
4-6	 <b>BS1A6S</b> Block Spade		
4-6	 <b>BS1A6</b>		
8	 <b>BS1A8</b>		

DIMENSIONAL CHART		
Part Number	W	L
B1A		0.570"
BS1A10	0.314"	0.615"
BS1A6	0.293"	0.619"
BS1A6S	0.246"	0.625"
BS1A8	0.312"	0.642"
R1A10	0.310"	0.697"
R1A14	0.530"	0.943"
R1A14S	0.460"	0.907"
R1A38	0.530"	0.940"
R1A56	0.531"	0.938"
R1A56S	0.460"	0.906"
R1A6	0.254"	0.642"
R1A6S	0.224"	0.545"
R1A8	0.313"	0.702"

Add suffix "M" for 1000 pack  
Add suffix "P" for Pro Pack (Quantities vary by Part #)

Approved installation tool: See tool chart pages E-2,3,4  
Economy installation tools: RAT-NINS, 453, HTS1000  
See pages E-2 to E-4 for installation tools.

**B**