

# CABLE TIE

## ASSORTMENT

A

Three  
Compartments  
with Resealable  
Access Doors



Total Ties	Part no.	Cable Tie Part no.	Ties Per Pac	Colour & Material	Tie Length		Tie Tensile	Bundle Diameter	UL-CSA	Military Specification	Per Case	ANSI/UL 62275 TYPE
					Inch	Pac						
400	TECHPAC4009	L-11509	100	Natural Nylon	11.2	285	50lb	1/16 - 3	UL-CSA	MS3367-7-9	20	21
Clam Shell Dimensions: 14 x 7-1/8" x 2" PVC		L-7509			7.5	190		1/16 - 1-3/4		MS3367-1-9		
		L-4189			4.0	102		1/16 - 7/8		MS3367-4-9		
400	TECHPAC4000	L-11500	100	UV Black Nylon	11.2	285	50lb	1/16 - 3	UL-CSA	MS3367-7-0	20	21
Clam Shell Dimensions: 14 x 7-1/8" x 2" PVC		L-7500			7.5	190		1/16 - 1-3/4		MS3367-1-0		
		L-4180			4.0	102		1/16 - 7/8		MS3367-4-0		

- Sold in case quantities only
- 20/case

## CABLE TIE INSTALLATION TOOLS



QC100

A lightweight tool for least critical applications. Cinch tie to desired bundle and twist tool to remove excess strap. Recommended for use with 18 – 50 pound ties.



L400

Tool for use with 18 – 50 pound ties. Automatic cut-off and adjustable tensioning for dependable use in assembly applications.



L200

Tool for use with 18 – 50 pound ties. Automatic cut-off removes excess strap flush against cable tie head. Tool is equipped with adjustable tensioning.



L300

Rugged construction makes this tool ideal for use with our 120 – 175 pound ties. Cinch tie to desired bundle and pull trigger to cut excess flush at Cable Tie head.

Field proven durability.