

Loom & Tubing Accessories (Clamps, Clips)

Vinyl Coated Steel Clamps

- Provides electrical insulation, vibration absorption, and protection of wire & cable, hydraulic hoses and loom/tubing from abrasion & shock
- Holds lines firmly in place
- **Insulation:** Clamps are dipped in PVC to provide excellent resistance to acids, moisture and salts.
- Contact Techspan if you require other sizes

D



Metal Width: 1/2" (12.7mm); Hole Diameter: 1/4"

ID Size	Actual Mounting Hole Diameter	Metal Thickness	10 PCS/PK	100 PCS/PK	500 PCS/PK
1/4" (6.4mm)	.268" (6.80mm)	0.8mm	766087	766087C	766087B
3/8" (9.5mm)	.268" (6.80mm)	0.8mm	766088	766088C	766088B
1/2" (12.7mm)	.268" (6.80mm)	0.8mm	766089	766089C	766089B
5/8" (15.9mm)	.268" (6.80mm)	0.8mm	766090	766090C	
3/4" (19.1mm)	.268" (6.80mm)	0.8mm	766091	766091C	766091B
1" (25.4mm)	.268" (6.80mm)	0.8mm	766092	766092C	
1-1/4" (31.8mm)	.268" (6.80mm)	0.8mm	766096	766096C	
1-1/2" (38.1mm)	.268" (6.80mm)	0.8mm	766093	766093C	
2" (50.8mm)	.268" (6.80mm)	0.8mm	766097	766097C	



Metal Width: 5/8" (15.9mm); Hole Diameter: 3/8"

ID Size	Actual Mounting Hole Diameter	Metal Thickness	10 PCS/PK	100 PCS/PK
1/4" (6.4mm)	.404" (10.25mm)	0.8mm	766058	766058C
3/8" (9.5mm)	.404" (10.25mm)	0.8mm	766074	766074C
1/2" (12.7mm)	.404" (10.25mm)	0.8mm	766059	766059C
5/8" (15.9mm)	.404" (10.25mm)	0.8mm	766075	766075C
3/4" (19.1mm)	.404" (10.25mm)	0.8mm	766060	766060C

Metal Width: 1" (25.4mm); Hole Diameter: 1/2"

ID Size	Actual Mounting Hole Diameter	Metal Thickness	10 PCS/PK	100 PCS/PK	500 PCS/PK
1" (25.4mm)	.531" (13.55mm)	1.1mm	766061	766061C	766061B

Vinyl Coated Steel Clamps



72-Hour Salt Spray Test

Why the change to Stainless Steel?

Material	Result
Zinc Electroplated Steel (previous version)	Subject to overall corrosion
Standard Grade Stainless Steel	Only minor corrosion on the edges
304-Grade Stainless Steel	No corrosion

