

Loom & Tubing Accessories (Clamps, Clips)

Rubber Insulated Steel Clamps

- Provides electrical insulation, vibration absorption, and protection of wire & cable, hydraulic hoses and loom from abrasion & shock
- Holds lines firmly in place
- Standard-Grade Stainless Steel for longer life
- **Insulation:** Black Silicone Rubber is very flexible and provides superior heat resistance. Temperature range: -40°C to 150°C (-40°F to 302°F)
- Contact Techspan if you require other sizes

Metal Width: 1/2" (12.7mm); Hole Diameter: 1/4"

ID Size	Actual Mounting Hole Diameter	Metal Thickness	10 PCS/PK	100 PCS/PK	500 PCS/PK
1/4" (6.4mm)	.268" (6.80mm)	0.8mm	766321	766321C	766321B
3/8" (9.5mm)	.268" (6.80mm)	0.8mm	766322	766322C	766322B
1/2" (12.7mm)	.268" (6.80mm)	0.8mm	766323	766323C	766323B
5/8" (15.9mm)	.268" (6.80mm)	0.8mm	766324	766324C	
3/4" (19.1mm)	.268" (6.80mm)	0.8mm	766325	766325C	
7/8" (22.2mm)	.268" (6.80mm)	0.8mm	766326	766326C	
1" (25.4mm)	.268" (6.80mm)	0.8mm	766327	766327C	
1-1/8" (28.6mm)	.268" (6.80mm)	0.8mm	766328	766328C	
1-1/4" (31.8mm)	.268" (6.80mm)	0.8mm	766329	766329C	
1-1/2" (38.1mm)	.268" (6.80mm)	0.8mm	766347		
2" (50.8mm)	.268" (6.80mm)	0.8mm	766348		
3" (76.2mm)	.268" (6.80mm)	0.8mm	766346		



D

Metal Width: 5/8" (15.9mm); Hole Diameter: 3/8"

ID Size	Actual Mounting Hole Diameter	Metal Thickness	10 PCS/PK	100 PCS/PK
1/4" (6.4mm)	.404" (10.25mm)	0.8mm	766330	766330C
3/8" (9.5mm)	.404" (10.25mm)	0.8mm	766331	766331C
1/2" (12.7mm)	.404" (10.25mm)	0.8mm	766332	766332C
5/8" (15.9mm)	.404" (10.25mm)	0.8mm	766333	766333C
3/4" (19.1mm)	.404" (10.25mm)	0.8mm	766334	766334C
7/8" (22.2mm)	.404" (10.25mm)	0.8mm	766335	766335C
1" (25.4mm)	.404" (10.25mm)	0.8mm	766336	766336C
1-1/8" (28.6mm)	.404" (10.25mm)	0.8mm	766337	766337C
1-1/4" (31.8mm)	.404" (10.25mm)	0.8mm	766338	766338C
1-1/2" (38.1mm)	.404" (10.25mm)	0.8mm	766339	766339C
2" (50.8mm)	.404" (10.25mm)	0.8mm	766340	766340C
2-1/2" (63.5mm)	.404" (10.25mm)	0.8mm	766341	766341C
3" (76.2mm)	.404" (10.25mm)	0.8mm	766342	766342C

Rubber Insulated Steel Clamps

Rubber Insulated Stainless Steel Clamps

- Provides electrical insulation, vibration absorption, and protection of wire & cable, hydraulic hoses and loom from abrasion & shock
- Holds lines firmly in place
- 304-Grade Stainless Steel will not rust or corrode
- **Insulation:** Black Silicone Rubber is very flexible and provides superior heat resistance. Temperature range: -40°C to 150°C (-40°F to 302°F)
- Contact Techspan if you require other sizes

Metal Width: 1/2" (12.7mm); Hole Diameter: 1/4"

ID Size	Actual Mounting Hole Diameter	Metal Thickness	10 PCS/PK	100 PCS/PK
1/4" (6.4mm)	.268" (6.8mm)	0.8mm	766351	766351C
3/8" (9.5mm)	.268" (6.8mm)	0.8mm	766352	766352C
1/2" (12.7mm)	.268" (6.8mm)	0.8mm	766353	766353C
5/8" (15.9mm)	.268" (6.8mm)	0.8mm	766354	766354C
3/4" (19.1mm)	.268" (6.8mm)	0.8mm	766355	766355C
7/8" (22.2mm)	.268" (6.8mm)	0.8mm	766356	766356C
1" (25.4mm)	.268" (6.8mm)	0.8mm	766357	766357C
1-1/4" (31.8mm)	.268" (6.8mm)	0.8mm	766368	766368C
1-1/2" (38.1mm)	.268" (6.8mm)	0.8mm	766369	766369C
2" (50.8mm)	.268" (6.8mm)	1.0mm	766370	766370C



Rubber Insulated Stainless Steel Clamps