

Heat Shrink Tubing


Dual Wall (Adhesive-Lined) Heat Shrink Tubing (Continued)



i "You Choose how Clear you want your Dual Wall (Adhesive-Lined) Heat Shrink Tubing!"

Why Use Clear Transparent Dual Wall (Adhesive-Lined) Heat Shrink?

- Provides optimal clarity for visual inspection
- Adhesive-lined, Dual Wall tubing ensures a waterproof seal
- Wire gauge is imprinted on the tubing to simplify size identification



- 3:1 shrink ratio
- Adhesive inner wall provides superior sealing against water, moisture and other contaminants
- Excellent for coverage of irregularly shaped connectors and components
- Will bond to plastics, rubber, neoprene, steel and polyethylene
- Provides added strain relief and sealing of terminals and connectors
- Electrical insulation of simple in-line splices
- Abrasion-resistant for tubes and pipes
- Can also be used to repair damaged wire harnesses
- Flame retardant

E



Dual Wall (Adhesive-Lined) Heat Shrink Tubing – 4FT Lengths

Dual Wall (Adhesive-Lined) Heat Shrink Tubing (Clear, Translucent)

- Made of adhesive-lined, cross-linked polyolefin that is flexible and easy to work with
- Operating temperature: -45°C to +125°C
- Minimum shrink temperature: 120°C

Expanded ID (Trade Size)	Recovered/ Shrunk ID (Approx)	Use with Wire Size (Approx)	Length	Pkg Qty	Pkg Type	Part#
1/8"	3/64"	22-18GA	4FT	5 pcs	Box	769684
1/8"	3/64"	22-18GA	4FT	50 pcs	Box	*769684B <i>*NEW</i>
3/16"	1/16"	20-12GA	4FT	5 pcs	Box	769685
3/16"	1/16"	20-12GA	4FT	50 pcs	Box	*769685B <i>*NEW</i>
1/4"	3/32"	16-10GA	4FT	5 pcs	Box	769686
1/4"	3/32"	16-10GA	4FT	25 pcs	Box	*769686B <i>*NEW</i>
3/8"	1/8"	12-6GA	4FT	5 pcs	Box	769687
3/8"	1/8"	12-6GA	4FT	25 pcs	Box	*769687B <i>*NEW</i>
1/2"	3/16"	8-2GA	4FT	5 pcs	Box	769688
1/2"	3/16"	8-2GA	4FT	25 pcs	Box	*769688B <i>*NEW</i>
3/4"	1/4"	4-2/0GA	4FT	5 pcs	Box	769689
3/4"	1/4"	4-2/0GA	4FT	10 pcs	Box	*769689B <i>*NEW</i>
1"	11/32"	2-4/0GA	4FT	5 pcs	Box	769690
1"	11/32"	2-4/0GA	4FT	10 pcs	Box	*769690B <i>*NEW</i>
1-1/2"	17/32"	4/0GA-250MCM	4FT	5 pcs	Box	769659

Heating Tools can be found on pages 146-147

Dual Wall (Adhesive-Lined) Heat Shrink Tubing (Clear, Transparent)

- Made of adhesive-lined, cross-linked ionic polymer
- Operating temperature: -55°C to +125°C
- Minimum shrink temperature: 90°C



Expanded ID	Recovered/ Shrunk ID (Approx)	Use with Wire Size (Approx)	Length	Pkg Qty	Pkg Type	Part#
0.176"	0.045"	22-18GA	6"	6 pcs	Bag	669654
0.250"	0.080"	16-14GA	6"	6 pcs	Bag	669655
0.365"	0.100"	12-10GA	6"	6 pcs	Bag	669656

Heating Tools can be found on pages 146-147