

Battery Cable Assemblies



New Packaging for Battery Cable Assemblies

If you require any different sizes of Battery Cable Assemblies, call Techspan

F



Top Post Battery Cables

- Made of quality copper conductor with cast lead universal terminals
- Full gauge stranded copper core is flexible for easy installation and allows maximum current
- Copper core extends to the end of the plated lug to give a one piece solid connection
- Colour-coded PVC insulation
- Meets SAE standards

Top Post Battery Cables

Fits up to 3/8" stud. Without Lead.

Length	Gauge	Red	Black
12" (305mm)	6GA	767622	
10" (254mm)	4GA	767821	767721
12" (305mm)	4GA	767822	767722
15" (381mm)	4GA	767823	767723
20" (508mm)	4GA	767825	767725
25" (635mm)	4GA	767826	767726
32" (813mm)	4GA	767828	767728
34" (863mm)	4GA	767829	767729
38" (965mm)	4GA	767830	767730
43" (1092mm)	4GA	767831	767731
48" (1219mm)	4GA	767832	767732
53" (1346mm)	4GA	767833	767733
56" (1422mm)	4GA	767834	767734
65" (1651mm)	4GA	767836	767736
72" (1829mm)	4GA	767837	767737
15" (381mm)	2-1GA		767122
20" (508mm)	2-1GA		767125
23" (584mm)	2-1GA		767126
32" (813mm)	2-1GA		767128
43" (1092mm)	2-1GA		767131
58" (1473mm)	2-1GA		767135
65" (1651mm)	2-1GA		767136
12" (30.5cm)	2/0GA		769380
24" (61.0cm)	2/0GA		769381
36" (91.4cm)	2/0GA		769382
48" (122.0cm)	2/0GA		769383
60" (152.4cm)	2/0GA		769384
72" (182.8cm)	2/0GA		769385

Fits up to 3/8" stud. With 1 auxiliary Lead (6", 12GA)

20" (508mm)	4GA	767853	767753
25" (635mm)	4GA	767854	767754
32" (813mm)	4GA	767856	767756
38" (965mm)	4GA	767858	767758
43" (1092mm)	4GA	767859	767759
48" (1219mm)	4GA	767860	767760
53" (1346mm)	4GA	767861	767761
65" (1651mm)	4GA	767863	767763



Top Post Battery Cables with Auxiliary Lead