

Toggle Switches

Medium-Duty Toggle Switches (Weather-Resistant)

Standard 11/16" 'Bat' Handle. Mounting stem: 15/32". Rating 20A @ 12VDC



765010

Feature	Benefit
O-Ring Seal + Plastic Coating	Weatherproofs the switch
ON/OFF Face Plate	Easily identifies the current function of switch
Wire Leads – Tin Plated Copper (14GA, 8" Long)	Tin Plating on the copper conductors prolong the life of the switch

Type	Description	1 PC/PK	25 PCS/PK	
2 Position (ON-OFF)	SPST	765010	765010B	
3 Position (Mom ON-OFF-Mom ON)	SPDT	*765018	*765018B	*NEW



765018

G

Light-Duty Toggle Switches


The best combination of space-saving size and economy for universal, lighter duty applications. CUL approval, where shown. Each switch comes with a Face Plate imprinted with an ON-OFF Face Plate.



765075

S.P.S.T. (Single Pole – Single Throw)

Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/ Type	Mounting Stem Diameter	Description	1 PC/PK	25 PCS/PK	
2	ON-OFF	2 Screws	35A @ 6VDC 20A @ 12VDC	Chrome, 'Bat'-style handle – 11/16" Long	7/16" Dia.	Brass Housing	765075	765075B	
2	ON-OFF	2 Blades	15A @ 120VAC 10A @ 240VAC	Chrome, 'Bat'-style handle – 16mm Long	15/32" Dia.		765072	765072B	
2	ON-OFF	2 Wires	6A @ 125VAC 3A @ 250VAC	Chrome, 'Bat'-style handle – 16mm Long	15/32" Dia.		765073	765073B	
2	ON-OFF	2 Wires	6A @ 125VAC 3A @ 250VAC	Chrome, 'Ball'-tip handle – 11mm Long	15/32" Dia.		*765077	*765077B	*NEW



765072



765073



*765077

