

# Battery Master Disconnect Switches

## Turn Lever

- IP66
- Ignition-Protected
- 4-Hole Mount
- Non-metallic, weather-resistant housing
- Removable protective cap
- Key is removable in the OFF position




Removable Cap




Removable Key



4 Mounting Holes



Circuit Diagram  
(765214 only)



Mounting Specifications (mm)

G



\*765214

## Lighted Actuator (Red)



\*765214 \*NEW

- S.P.S.T
- ON-OFF
- LED lights up continuously at all positions when power is inputted from Terminal 1 and only at the ON position when power is inputted from Terminal 2
- 12-24VDC
- Continuous Rating: 300A @ 12VDC, 150A @ 24VDC
- Intermittent Rating: 450A @ 12VDC, 225A @ 24VDC (5 minutes)
- Crank Rating: 1000A @ 12VDC, 800A @ 24VDC (10 seconds)
- 3 Terminals (2 x 3/8" Screws, 1 x 1/4" Blade)



\*765208



765214  
Red LED Indicator  
on Actuator

\*765208 \*NEW  
\*765208B \*NEW

Replacement key for Part # 765214 & 765228  
Same as above, except 25 PCS/PK

## Standard (Red, Non-Lit) Actuator

765218

- S.P.S.T
- ON-OFF
- 12VDC
- Continuous Rating: 350A @ 12VDC
- Intermittent Rating: 500A @ 12VDC (5 minutes)
- Crank Rating: 1000A @ 12VDC, 800A @ 24VDC (10 seconds)
- 2 x 3/8" Screw Terminals



765218

765217  
765217B

Replacement key for Part # 765218  
Same as above, except 25 PCS/PK



765217