

Solenoids

Solenoids

- S.P.S.T. • Continuous-Duty
- Normally Open Contacts (Normally OFF)
- OFF-ON

Steel Housing; 100A Continuous, 150A in Rush

| Voltage | # of Studs | 1 PC/PK | 10 PCS/PK |
|---------|------------|---------|-----------|
| 12V | 3 | *765202 | *765202B |



*765202

Steel Housing; 85A Continuous, 150A in Rush

| Voltage | # of Studs | 1 PC/PK | 10 PCS/PK |
|---------|------------|---------|-----------|
| 12V | 4 | 765204 | 765204B |
| 24V | 4 | 765203 | 765203B |



765204



765203

Coated Steel Housing; 100A Continuous, 150A in Rush

| Voltage | # of Studs | 1 PC/PK |
|---------|------------|---------|
| 12V | 4 | 765206 |

UL Listed



765206



Trombetta Solenoids



- SPST (Single Pole, Single Throw)
- Normally Open Contacts (Normally Off)
- OFF-ON
- Plastic Housing
- IP67 (Water & Dust Ingress Protection)

- 5/16-24 Contact Studs, 10-32 Studs Coil Terminals
- Mount only with the studs up or parallel with the terrain, never down
- Also known as DC Contactors

- Do not exceed the maximum torque ratings on the item label
- **Note:** Continuous-Duty & Intermittent-Duty are not interchangeable

150A Continuous-Duty, 800A in Rush, Non-Grounded

| Voltage | Bracket Type | 1 PC/PK | 12 PCS/PK | Trombetta # |
|---------|--------------|---------|-----------|--------------|
| 12VDC | Flat Bracket | *765198 | *765198B | 684-1221-012 |

150A Intermittent-Duty, 800A in Rush, Non-Grounded

| Voltage | Bracket Type | 1 PC/PK | 12 PCS/PK | Trombetta # |
|---------|------------------|---------|-----------|--------------|
| 12VDC | Flat 'L' Bracket | *765201 | *765201B | 684-1251-212 |

150A Intermittent-Duty, 800A in Rush, Non-Grounded

| Voltage | Bracket Type | 1 PC/PK | 12 PCS/PK | Trombetta # |
|---------|----------------------------|---------|-----------|--------------|
| 12VDC | Curved, Narrow 'L' Bracket | *765196 | *765196B | 684-1261-212 |



*765198
(Flat Bracket)



*765201
(Flat 'L' Bracket)



*765196
(Curved, Narrow 'L' Bracket)