

Solder/Shrink Terminals & Connectors

The solder splice connectors consist of a fluxed solder ring with a heat shrinkable insulation sleeve which, when heated, provides a completely soldered, strain relieved, and encapsulated termination. Heating tools can be found pages 146-147

c  Where Indicated

A

Butt Connectors (Solder/Shrink)

22-22GA



c 

761670 25 pk
761670B 500 pk

22-18GA



691671 5 pk c 

761671 25 pk
761671B 500 pk

16-14GA



691672 5 pk c 

761672 25 pk
761672B 500 pk

12-10GA



691673 5 pk c 

761673 25 pk
761673B 500 pk

Ring Terminals (Solder/Shrink)

22-18GA



Stud Size #6 c 

761674 25 pk
761674B 500 pk



Stud Size #8 c 

761675 25 pk
761675B 500 pk



Stud Size #10 c 

761676 25 pk



Stud Size 12-1/4" c 

761677 25 pk

16-14GA



Stud Size #8 c 

761678 25 pk
761678B 500 pk



Stud Size #10 c 

761679 25 pk
761679B 500 pk



Stud Size 12-1/4" c 

761680 25 pk
761680B 500 pk



Stud Size 3/8" c 

761681 25 pk

12-10GA



Stud Size #10 c 

761682 25 pk
761682B 500 pk



Stud Size 12-1/4" c 

761683 25 pk
761683B 500 pk



Stud Size 3/8" c 

761684 25 pk
761684B 500 pk



Stud Size 1/2" c 

761685 25 pk

Spade/Fork Terminals (Solder/Shrink)

22-18GA



Stud Size #10 c 

761686 25 pk
761686B 500 pk

16-14GA



Stud Size #10 c 

761687 25 pk
761687B 500 pk

12-10GA



Stud Size #10 c 

761688 25 pk

Quick Disconnects/Slide Connectors (Solder/Shrink)

22-18GA



Tab Size 0.25" Female

761689 25 pk
761689B 500 pk

16-14GA



Tab Size 0.25" Female

761691 25 pk

12-10GA



Tab Size 0.25" Female

761693 25 pk
761693B 500 pk

22-18GA



Tab Size 0.25" Male

761690 25 pk
761690B 500 pk

16-14GA



Tab Size 0.25" Male

761692 25 pk
761692B 500 pk

12-10GA



Tab Size 0.25" Male

761694 25 pk
761694B 500 pk