Crimp/Solder/Shrink Terminals & Connectors

c UL Where Indicated

Spade/Fork Terminals (Crimp/Solder/Shrink)

ACTUAL SIZE PICTURES

22-18GA

Stud Size #6 c UL

761779	25 pk
761779B	500 pk

Stud Size #8 c UL

761782	25 pk

Stud Size #10 c UL

761785	25 pk

16-14GA

Stud Size #6 c UL

761780	25 pk

Stud Size #8 c UL

761783	25 pk

Stud Size #10 c UL

761786	25 pk

12-10GA

Stud Size #6 c UL

761781	25 pk

Stud Size #8 c UL

761784	25 pk
761784B	500 pk

Stud Size #10 c UL

761787	25 pk

Quick Disconnects/Slide Connectors (Crimp/Solder/Shrink)

ACTUAL SIZE PICTURES

22-18GA

Female quick disconnect
Fully Insulated, Tab Size: 0.25"

761773	25 pk

16-14GA

Female quick disconnect
Fully Insulated, Tab Size: 0.25"

761774	25 pk
761774B	500 pk

12-10GA

Female quick disconnect
Fully Insulated, Tab Size: 0.25"

761775	25 pk

22-18GA

Male quick disconnect
Tab Size: 0.25"

761776	25 pk

16-14GA

Male quick disconnect
Tab Size: 0.25"

761777	25 pk
761777B	500 pk

12-10GA

Male quick disconnect
Tab Size: 0.25"

761778	25 pk

Crimp Tools for Heat Shrink Terminals can be found on page 19. Heating tools are on pages 146-147