

A

Nylon Insulated Terminals & Connectors

Terminals and connectors with tin plated annealed copper construction are specifically designed for heavy-duty applications where both high temperatures and vibration levels are encountered. Nylon sleeves offer maximum crimp strength; many nylon terminals are double crimp style, one crimp on the bare wire for connection and one crimp on the wire insulation. Operating temperatures: -55°C to 105°C. 600 Volt rating. Crimp tools can be found on pages 47-49




Professional Packs



Cost-Saving Bulk Pack


Nylon Insulated Butt Connectors

22-18GA




691497	10 pk
761497	100 pk
761497M	1000 pk

16-14GA



691498	10 pk
761498	100 pk
761498M	1000 pk

12-10GA



691513	8 pk
761513	100 pk
761513M	1000 pk

Nylon Insulated Quick Disconnects/Slide Connectors

22-18GA



Female quick disconnect Fully Insulated, Tab Size 0.187"	
761321	100 pk
761321M	1000 pk



Male quick disconnect Fully Insulated, Tab Size 0.187"	
761320	100 pk
761320M	1000 pk



Female quick disconnect Fully Insulated, Tab Size 0.25"	
761354	50 pk
761354M	1000 pk



Male quick disconnect Fully Insulated, Tab Size 0.25"	
761353	50 pk
761353M	1000 pk

16-14GA



Female quick disconnect Fully Insulated, Tab Size 0.187"	
761323	100 pk
761323M	1000 pk



Male quick disconnect Fully Insulated, Tab Size 0.187"	
761322	100 pk



Female quick disconnect Fully Insulated, Tab Size 0.25"	
691357	5 pk
761357	50 pk
761357M	1000 pk



Male quick disconnect Fully Insulated, Tab Size 0.25"	
691358	5 pk
761358	50 pk
761358M	1000 pk

12-10GA



Female quick disconnect Fully Insulated, Tab Size 0.25"	
691623	7 pk
761623	50 pk
761623M	1000 pk



Male quick disconnect Fully Insulated, Tab Size 0.25"	
691621	7 pk
761621	50 pk
761621M	1000 pk

16-14GA




Female quick disconnect Tab Size 0.25"	
761444	100 pk
761444M	1000 pk




Male quick disconnect Tab Size 0.25"	
761445	100 pk
761445M	1000 pk

A look inside Fully Insulated Quick Disconnect/Slide Connector



Female quick disconnect



Male quick disconnect

12-10GA



Female quick disconnect Tab Size 0.25"	
761496	50 pk



Male quick disconnect Tab Size 0.25"	
761495	50 pk