

Lighting & Safety Equipment

High Intensity (Senior) Beacons/Strobes – Aluminum Base

- Aluminum Base
- Polycarbonate Lens
- Clear Outer Dome
- Dimensions: 7.88" H x 8.63" Base Diameter
- Surface Mount
- Mounting Options: 3-1/2" Centre or 7" Centre
- Fully Encapsulated Circuitry
- Pre-installed hardware saves time & money
- Mounting bracket provided
- Encapsulated circuitry and fewer holes on body will prevent moisture from getting into the unit

Part#	Description	Qty/Pkg
745400	Amber Lens, 12-24VDC, 17 Joules, 2.3A @ 12V. Flash Pattern Options: Double / Quad Flash (SAE J845 Class 2)	1 PC
745258	Discontinued – Replaced by #745258LED Blue Lens, 12-48VDC, 14 Joules, 2.00A @ 12V. Flash Pattern Options: Single Flash (SAE J1318 Class 3) / Quad Flash (SAE J1318 Class 2)	1 PC
*NEW *745258LED	LED, Blue Diodes, Blue Lens, 12-36VDC, 4.9A @ 12V, Flash Pattern Options: Single, Double, Triple, Quad, Rotating (96 or 126 RPM). SAE J845 (Class 2)	1 PC



745400



***745258LED**

REPLACEMENT PARTS FOR 745400

735186AMB	Replacement Flashtube for 745400	1 PC
731981	Replacement Clear Outer Dome (Polycarbonate) for 745400	1 PC
731982	Replacement Inner Amber Lens (Polycarbonate) for 745400	1 PC

High Voltage LED Beacons

LED



- 120VAC (0.1A)
- Plastic Base
- Polycarbonate (Sonic Welded) Lens
- IP66
- Dimensions: 4.6" Diameter x 4" H
- Flange Mount & Optional 1/2" NPT Pipe Mount Socket. Pipe not included
- UL Listed

Colour	Flash Pattern	Previous Techspan #	Part #
 Red	60 Single Flashes per minute	745000	*745000LED
 Amber	60 Single Flashes per minute	745001	*745001LED
 Blue	60 Single Flashes per minute	745002	*745002LED
 Green	60 Single Flashes per minute	745003	*745003LED
 Amber	Flashing & Rotating	–	*745004



745000LED



745001LED



745002LED



745003LED



745004

**Now
manufactured
with an LED
light source!**

Fit/Form/Function
is identical

K