

Terminals & Connectors (K-Spec® Series)

Fully Insulated Quick Disconnects/Slide Connectors (K-Spec® Series)



300V Rating, Brass. Nylon (105°C). PVC (75°C)

22-18GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561354 100 pk
561354D 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561353 100 pk
561353D 500 pk

22-18GA



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"
561345 100 pk
561345D 500 pk

16-14GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561357 100 pk
561357D 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561358 100 pk
561358D 500 pk

16-14GA



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"
561346 100 pk
561346D 500 pk

12-10GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561623 100 pk
561623D 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"
561621 100 pk
561621D 500 pk

12-10GA



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"
561347 100 pk
561347D 500 pk

PVC Insulated Piggy Back Connectors (K-Spec® Series)



300V Rating, 75°C, Brass

22-18GA



562415 100 pk
562415D 500 pk

16-14GA



562416 100 pk
562416D 500 pk

12-10GA



562399 100 pk
562399D 500 pk

Nylon Insulated Female Flag Connectors (K-Spec® Series)



300V Rating, 105°C, Copper

22-18GA



.187" x .032"
562398 100 pk
562398D 500 pk



.250" x .032"
562407 100 pk
562407D 500 pk

16-14GA



.250" x .032"
562408 100 pk
562408D 500 pk