

TEW Wire

For use in internal wiring of electrical and electronic equipment. Applications include electric ranges, heating equipment, lighting fixtures, panels and meters. CSA & UL Approved. For applications up to 600 Volts. Copper conductors are stranded with PVC Insulation. Temperature Rating: -40°C to 105°C (-40°F to 221°F). Available with bare copper or tin-plated copper conductors.



B



TEW Wire – Bare Copper Conductors: 30m (98.4') Spools

GA	O.D.	Stranding	Black	Blue	Brown	Green	Grey	Orange	Purple	Red	White	Yellow
18	.109"	16 x .010"	768600	768601	768602	768603	768608	768604	768599	768605	768606	768607
16	.122"	26 x .010"	768609	768610	768611	768612	768617	768613	768598	768614	768615	768616
14	.136"	41 x .010"	768618	768619	768620	768621	768626	768622	768597	768623	768624	768625
12	.159"	65 x .010"	768627	768628	768629	768630	768635	768631	768596	768632	768633	768634
10	.183"	105 x .010"	768636	768637	768638	768639		768640		768641	768642	768643

O.D. = Outside Diameter

TEW Wire – Bare Copper Conductors: 300m (984') Spools

GA	O.D.	Stranding	Black	Blue	Brown	Green	Grey	Orange	Purple	Red	White	Yellow
18	.109"	16 x .010"	768600M	768601M	768602M	768603M	768608M	768604M	768599M	768605M	768606M	768607M
16	.122"	26 x .010"	768609M	768610M	768611M	768612M	768617M	768613M	768598M	768614M	768615M	768616M
14	.136"	41 x .010"	768618M	768619M	768620M	768621M	768626M	768622M	768597M	768623M	768624M	768625M
12	.159"	65 x .010"	768627M	768628M	768629M	768630M	768635M	768631M	768596M	768632M	768633M	768634M
10	.183"	105 x .010"	768636M	768637M	768638M	768639M		768640M		768641M	768642M	768643M

O.D. = Outside Diameter



TEW Wire – Tinned Copper Conductors: 30m (98.4') Spools

GA	O.D.	Stranding	Black	Blue	Brown	Green	Grey	Orange	Purple	Red	White	Yellow
18	.109"	16 x .010"	768654	768655	768656	768657	768663	768658	768662	768659	768660	768661
16	.122"	26 x .010"	768664	768665	768666	768667	768673	768668	768672	768669	768670	768671
14	.136"	41 x .010"	768674	768675	768676	768677	768683	768678	768682	768679	768680	768681
12	.159"	65 x .010"	768684	768685	768686	768687	768693	768688	768692	768689	768690	768691
10	.183"	105 x .010"	768694	768695	768696	768697	768703	768698	768702	768699	768700	768701

O.D. = Outside Diameter

TEW Wire – Tinned Copper Conductors: 300m (984') Spools

GA	O.D.	Stranding	Black	Blue	Brown	Green	Grey	Orange	Purple	Red	White	Yellow
18	.109"	16 x .010"	768654M	768655M	768656M	768657M	768663M	768658M	768662M	768659M	768660M	768661M
16	.122"	26 x .010"	768664M	768665M	768666M	768667M	768673M	768668M	768672M	768669M	768670M	768671M
14	.136"	41 x .010"	768674M	768675M	768676M	768677M	768683M	768678M	768682M	768679M	768680M	768681M
12	.159"	65 x .010"	768684M	768685M	768686M	768687M	768693M	768688M	768692M	768689M	768690M	768691M
10	.183"	105 x .010"	768694M	768695M	768696M	768697M	768703M	768698M	768702M	768699M	768700M	768701M

O.D. = Outside Diameter