



WHY CHOOSE RUBBER JACKETED BATTERY CABLE?

- ✓ Better Acid & Oil Resistance
- ✓ Extra Flexible
- ✓ Extra Durable

B

Battery Cable

Battery Cable – Rubber Jacketed

- 100% copper conductors, finely stranded
- Black or Red SGR Rubber Jacket (Extra Flexible)
- SAE specification J1127
- For applications up to 60 Volts
- Oil & acid resistant
- Excellent flame retardant characteristics
- Temperature Rating: -40°C to 90°C (-40°F to 194°F)



Rubber Jacketed Battery Cable – Black

Black

GA	O.D.	Stranding	25' (7.6m) Spool	100' (30.5m) Spool	500' (152.4m) Spool
6	.272"	7 x 19 x .014"	669266	769266	769266B
4	.370"	7 x 27 x .014"	669265	769265	769265B
2	.460"	19 x 16 x .014"	669262	769262	769262B
1	.495"	19 x 21 x .014"	669260	769260	769260B
1/0	.550"	19 x 26 x .014"	669261	769261	769261B
2/0	.595"	19 x 22 x .018"	669263	769263	769263B
3/0	.700"	19 x 35 x .016"	669267	769267	769267B
4/0	.760"	19 x 54 x .014"	669287	769287	769287B



Cost Saving Bulk Spools are now available in 500FT lengths



The following part numbers that had represented the 25 Foot Spools of Black Rubber Jacketed Battery Cable were changed, as follows:

Old Part#		New Part#
769256	⇒	669266
769255	⇒	669265
769252	⇒	669262
769250	⇒	669260
769251	⇒	669261
769253	⇒	669263
769284	⇒	669267
769286	⇒	669287

Red

GA	O.D.	Stranding	25' (7.6m) Spool	100' (30.5m) Spool	500' (152.4m) Spool
6	.272"	7 x 19 x .014"	669270	769270	769270B
4	.370"	7 x 27 x .014"	669271	769271	769271B
2	.460"	19 x 16 x .014"	669272	769272	769272B
1	.495"	19 x 21 x .014"	669273	769273	769273B
1/0	.550"	19 x 26 x .014"	669274	769274	769274B
2/0	.595"	19 x 22 x .018"	669275	769275	769275B
3/0	.700"	19 x 35 x .016"	669276	769276	769276B
4/0	.760"	19 x 54 x .014"	669277	769277	769277B



Rubber Jacketed Battery Cable – Red