

# Battery Cable

## Battery Cable – PVC Jacketed

- 100% copper conductors, finely stranded
- Black or Red PVC Insulation (Flexible)
- SAE specification J1127
- For applications up to 60 Volts
- Oil & acid resistant
- Excellent flame retardant characteristics
- Temperature Rating: -40°C to 90°C (-40°F to 194°F)

### WHY CHOOSE PVC JACKETED BATTERY CABLE?

- ✓ Acid & Oil Resistant
- ✓ Flexible
- ✓ Durable
- ✓ Economical



### Black

GA	O.D.	Stranding	25' (7.6m) Spool	100' (30.5m) Spool	500' (152.4m) Spool
6	.272"	7 x 19 x .014"	669225	769225	769225B
4	.370"	7 x 27 x .014"	669226	769226	769226B
2	.460"	19 x 16 x .014"	669227	769227	769227B
1	.495"	19 x 21 x .014"	669228	769228	769228B
1/0	.550"	19 x 26 x .014"	669229	769229	769229B
2/0	.595"	19 x 22 x .018"	669230	769230	769230B
3/0	.700"	19 x 35 x .016"	669231	769231	769231B
4/0	.760"	19 x 54 x .014"	669232	769232	769232B



PVC Jacketed Battery Cable – Black

### Red

GA	O.D.	Stranding	25' (7.6m) Spool	100' (30.5m) Spool	500' (152.4m) Spool
6	.272"	7 x 19 x .014"	669242	769242	769242B
4	.370"	7 x 27 x .014"	669243	769243	769243B
2	.460"	19 x 16 x .014"	669244	769244	769244B
1	.495"	19 x 21 x .014"	669245	769245	769245B
1/0	.550"	19 x 26 x .014"	669246	769246	769246B
2/0	.595"	19 x 22 x .018"	669247	769247	769247B
3/0	.700"	19 x 35 x .016"	669248	769248	769248B
4/0	.760"	19 x 54 x .014"	669249	769249	769249B



PVC Jacketed Battery Cable – Red



The following part numbers that had represented the 25 Foot Spools of Red PVC Jacketed Battery Cable were changed, as follows:

Old Part#		New Part#
769233	⇒	669242
769234	⇒	669243
769235	⇒	669244
769236	⇒	669245
769237	⇒	669246
769238	⇒	669247



Cost Saving Bulk Spools are now available in 500FT lengths