

## Welding Cable & Booster Cable Cord (Bonded)

**B**



Neoprene Jacketed Welding Cable – Black

### Welding Cable

- 100% copper conductors, finely stranded
- Extra Flexible Neoprene (EPDM) Jacket
- SAE specification J1127
- For applications up to 600 Volts
- Resists abrasion, cut, tear, flame, grease, oil and water
- Excellent flame retardant characteristics
- Temperature Rating: -50°C to 105°C (-58°F to 221°F)
- Also designed for all welding applications where a stinger/whip, leads and grounds are used



#### Black

GA	O.D.	Stranding	25' (7.6m) Spool	100' (30.5m) Spool	250' (76.2m) Spool
6	.320"	7/37/.010"	669285	769285	*769285-250
4	.348"	7/52/.010"	669288	769288	*769288-250
2	.420"	12/52/.010"	669298	769298	*769298-250
1	.503"	12/65/.010"	669297	769297	*769297-250
1/0	.533"	19/52/.010"	669292	769292	*769292-250
2/0	.586"	19/65/.010"	669291	769291	*769291-250
3/0	.625"	19/81/.010"	669289	769289	*769289-250
4/0	.720"	19/106/.010"	669290	769290	*769290-250



The following part numbers that had represented the 25 Foot Spools of Black Rubber Jacketed Welding Cable were changed, as follows:

Old Part#		New Part#
769296	⇒	669298
769295	⇒	669297
769293	⇒	669292
769294	⇒	669291



Neoprene Jacketed Welding Cable – Red




#### Red

GA	O.D.	Stranding	25' (7.6m) Spool	100' (30.5m) Spool	250' (76.2m) Spool
6	.320"	7/37/.010"	*669220	*769220	*769220-250
4	.348"	7/52/.010"	*669221	*769221	*769221-250
2	.420"	12/52/.010"	*669222	*769222	*769222-250
1	.503"	12/65/.010"	*669223	*769223	*769223-250
1/0	.533"	19/52/.010"	*669224	*769224	*769224-250
2/0	.586"	19/65/.010"	*669254	*769254	*769254-250
3/0	.625"	19/81/.010"	*669257	*769257	*769257-250
4/0	.720"	19/106/.010"	*669259	*769259	*769259-250




6GA

Make Your Own Booster Cables!



4GA



2GA

### Booster Cable Cord (Bonded)

- 100% copper conductors, finely stranded
- PVC & TPE Insulation provides a durable barrier to protect against abrasion, chemicals and the environment
- Tangle-free bonded cables are colour-coded for easy polarity identification
- SAE specification SAE J1127
- For applications up to 60 Volts

Jacket-Type	Gauge Sizes	Temperature Ratings
PVC Insulation	6GA, 4GA	-40°C to +80°C (-40°F to +176°F)
TPE Insulation	2GA	-40°C to +105°C (-40°F to +221°F)

GA	O.D.	Stranding	Jacketing	100' (30.5m)	500' (152.4m)	1200' (365.8m)
6	0.360"/0.780"	7 x 19/27	Black/Orange (PVC)	768429		768429B
4	0.410"/0.880"	7 x 19/25	Black/Red (PVC)	768428	768428B	
2	0.450"/0.960"	7 x 37/26	Black/Red (TPE)	768427	768427B	

Booster Cable Clamps can be found on page 173