

Booster Cable Assemblies



B

Booster Cables, 100% Copper

Techspan Premium Quality Booster Cables remain flexible at temperatures as low as -40°C (-40°F). Parallel bonded cables make these assemblies tangle-free. 100% pure copper for maximum conductivity.

Maximum Amperage	Length	GA Size	Clamp Type	Package Type	Part #
300A	12FT	8GA	Mechanic	Zippered Bag	769528
400A	16FT	6GA	Mechanic	Zippered Bag	769532
500A	20FT	4GA	Parrot	Storage Case	769533
700A	20FT	2GA	Parrot	Storage Case	769527
1000A	25FT	1GA	Mechanic	Storage Case	769526
900A	40FT	1GA	Mechanic	Pail	769530

Part #
 769526, 769527 &
 769533 are now
 supplied in
 a durable plastic
 storage case



769530 is supplied in a pail.

Booster Cables, CCA (Copper Clad Aluminum)

For applications where maximum conductivity is not required, assemblies with Copper Clad Aluminum (CCA) conductors are available. Parallel bonded cables allow for tangle-free use. All Techspan Booster Cables Assemblies remain flexible at temperatures as low as -40°C (-40°F).

Maximum Amperage	Length	GA Size	Clamp Type	Package Type	Part #
300A	16FT	6GA	Mechanic	Zippered Bag	569532
400A	20FT	4GA	Parrot	Zippered Bag	569533
500A	20FT	2GA	Parrot	Zippered Bag	569527
700A	25FT	1GA	Mechanic	Zippered Bag	569526



All other SKUs are supplied in zipper bags