

## Combination Warning & Tractor/Utility Lamp – LED

### Square Warning/Tractor/Utility Lamp – LED

(Amber Quad Flash or Steady White Light Modes) with Temperature Control System

**LED**



725261



Front/Angled View



Side View



Back View



Quad Flash (Amber)



White Light (Steady)

- 10-30VDC
- 54 Watts
- Die-Cast Aluminum Housing (Black)
- Back also functions as a built-in 'heat sink'
- Polycarbonate Lens
- Stainless Steel Hardware
- IP67
- Made with EMC Technology (Electro Magnetic Compatibility), meaning protection against Radio Frequency Interference (RFI)
- Dimensions: 3.98" W x 4.50" H x 1.77" D
- Stud Size: 10mm
- Pedestal Mount

**FEATURES A STROBE FUNCTION**

| Description        | Lumens | Current Draw                | Wattage                     | Light Beam Pattern     | 1 PC/PK |
|--------------------|--------|-----------------------------|-----------------------------|------------------------|---------|
| Quad Flash (Amber) | 1125   | 0.2A @ 12V,<br>0.1A @ 24V   | 9 Watts<br>(9 x 1W Diodes)  | Quad Flash             | 725261  |
| White Light        | 5400   | 3.64A @ 12V,<br>1.88A @ 24V | 45 Watts<br>(9 x 5W Diodes) | Wide Flood Beam (120°) |         |

**1125 Lumens**

**5400 Lumens**



### Rectangular Warning/Tractor/Utility Lamp – LED

(Amber Quad Flash and/or Steady White Light Modes)

**LED**



725262



Front/Angled View




Side View




Back View



Quad Flash (Amber)



Quad Flash (Amber) & White Light (Steady)



White Light (Steady)

- 10-30VDC
- 22.5 Watts
- Die-Cast Aluminum Housing (Black)
- Back also functions as a built-in 'heat sink'
- Polycarbonate Lens
- Stainless Steel Hardware
- IP67
- Made with EMC Technology (Electro Magnetic Compatibility), meaning protection against Radio Frequency Interference (RFI)
- Dimensions: 6.29" W x 1.80" H x 2.48" D
- Stud Size: 8mm
- Pedestal Mount

**FEATURES A STROBE FUNCTION**

| Description         | Lumens | Current Draw                | Wattage                         | Light Beam Pattern | 1 PC/PK |
|---------------------|--------|-----------------------------|---------------------------------|--------------------|---------|
| Quad Strobe (Amber) | 1125   | 0.2A @ 12V,<br>0.1A @ 24V   | 9 Watts<br>(9 x 1W Diodes)      | Quad Flash (Amber) | 725262  |
| White Light         | 1710   | 1.25A @ 12V,<br>0.62A @ 24V | 13.5 Watts<br>(9 x 1.5W Diodes) | Flood Beam (80°)   |         |

**1125 Lumens**

**1710 Lumens**

