

Tractor/Utility Lamps – LED Sealed Beams

LED PAR 36 (4-1/2" Round) Sealed Beam & Housing Assembly, with High-Low Settings

LED



725256

- Low Beam is a Flood Pattern, High Beam is a Spot Pattern
- 10-32VDC (1.6A @ 12V, 0.8A @ 24V)
- 40 Watts (8 x 5W Diodes)
- Die-Cast Aluminum Housing • Polycarbonate Lens
- IP67 • Dimensions: 4-7/8" Dia. x 5-7/8" H x 3"D
- Stud Size: 5/16" • Pedestal Mount

Clear Lens, Rubber Housing

Light Beam Pattern	Lumens	1 PC/PK
Combination Flood Beam (60°) & Spot Beam (30°)	2200 (Maximum)	725256



2200 Lumens

LED PAR 36 (4-1/2" Round) Sealed Beam Only, with High-Low Settings

Will Fit/Retrofit Into PAR 36 Housings



735459

- Low Beam is a Flood Pattern, High Beam is a Spot Pattern
- 10-32VDC (1.6A @ 12V, 0.8A @ 24V)
- 40 Watts (8 x 5W Diodes)
- Die-Cast Aluminum Housing
- Polycarbonate Lens • IP67

Clear Lens


Light Beam Pattern	Lumens	1 PC/PK
Combination Flood Beam (60°) & Spot Beam (30°)	2200 (Maximum)	735459



2200 Lumens



3 Male Terminals for High/Low Setting Selection



Back View



Front/Angled View



Side View

4-1/2" Round Housings for PAR 36 LED Sealed Beams



725045

Housing Only	Terminals	1 PC/PK	10 PCS/PK
Rubber	Slide Connectors/Quick Disconnects	725045	725045B



More Housings & Accessories Can Be Found In Our 154-page Lighting & Safety Equipment Catalogue