

Specialty Beacons

Mini LED Beacons

- Polycarbonate Base
- Polycarbonate Lens
- IP67
- Conforms to **SAE J845 Class 2**
(On applicable colours and flash patterns)
- Dimensions: 3.6" H x 5.1" Base Diameter



LED




Surface (Flange) Mount

- 10-110VDC (0.54A @ 12V, 0.02A @ 110V)
- 12 User-Selectable Flash Patterns
- 3 Mounting Holes with 4-3/4" centres

Now
Made For
Applications
Up To
110VDC!


Colour	Part#	Colour	Part#
Amber	*745357LED	Blue	*745358LED
Red	*745414LED	White	*745415LED



*745357LED



*745414LED



*745358LED



*745415LED

Magnetic Mount

- 12-24VDC (1.10A @ 12V, 0.47A @ 24V)
- 7 User-Selectable Flash Patterns
- 15FT Cord with a 12V Adapter Plug and 2 Rocker Switches – One for power, the other for flash pattern selection

Colour	Part#	Colour	Part#
Amber	*745359LED	Blue	*745360LED

Magnetic Mount option includes a 12V Adapter Plug with 2 integrated Rocker Switches



*745359LED



*745360LED

These Beacons previously had the following specs:

- 9-30VDC (0.2A @ 12V)
- 6.4 Watts (32 x 0.2W Diodes)
- Polycarbonate Base
- Polycarbonate Lens
- IP66
- 3 User Selectable Flash Patterns: Quad and Quint Flash, Rotating
- Dimensions: 3-3/4" H x 5" Base Diameter

Surface (Flange) Mount


- 3 Mounting Holes with 4-3/4" centres

Colour	Part#
Amber	745357

Magnetic Mount

- 12FT Cord with integrated Push Switch for power and flash pattern selection

Colour	Part#	Colour	Part#
Amber	745359	Blue	745360



745357



745359



745360