


WINGED WIRE CONNECTORS

B



DIMENSIONS:

Model	A		B		C		D		E	
	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)
WN734D	7.20	0.283	11.60	0.457	18.30	0.720	9.20	0.362	29.00	1.142
WN735D	9.00	0.354	13.50	0.531	23.00	0.906	9.60	0.378	31.80	1.252
WN736D	10.00	0.394	14.90	0.587	25.50	1.000	10.00	0.394	33.30	1.311

Model	Colour	Approval		Wire Range & Rating	Packing
WN734D	Tan			600 Volt / 300 Volt* Temp 105°C (221°F) No. 22 – No. 8 AWG Max. 3 #10 Min. 3 #22	Bag of 500
WN734J	Tan				Jar of 400
WN735D	Red			600 Volt / 300 Volt* Temp 105°C (221°F) No. 18 – No. 8 AWG Max. 5 #12 Min. 3 #16	Bag of 500
WN735J	Red				Jar of 250
WN736D	Grey			600 Volt Max.* Temp 105°C (221°F) No. 18 – No. 8 AWG Max. 3 #10 Min. 3 #14 w/1 #18	Bag of 500
WN736J	Grey				Jar of 175

* 1000 Volt Max. in lighting fixtures and signs

- UL 486C Listed and CSA Certified
- Plastic cap molded of tough thermoplastic UL 94V-2 flame-retardant material
- Five colour-coded to industry standards
- Socket tools are available for easy installation of wire connectors.



LISTED

Copper Solid and Stranded Wire Only