

JUNIOR PULLING GRIPS

Junior Pulling Grips are reusable tools designed for pulling cables, wire and rope. Constructed of galvanized steel mesh, these grips are designed for use in pulling single cable or bundled

cables in overhead, underground, electrical construction and industrial applications. Customized sizes and designs available.



Cable Range	Part #	Description	Approx.* Breaking Strength	Length Mesh
.25- .36	3305-002	JP-25	1700	5"
.37- .49	3305-003	JP-37	1700	7"
.50- .61	3305-004	JP-50	1700	8"
.62- .74	3305-005	JP-62	2800	10"
.75- .99	3305-006	JP-75	4100	10"
1.00-1.25	3305-007	JP-100	4100	12"
.25-1.25	3305-008	JPK-1 Kit includes: JP-25, JP-37 JP-50, JP-62, JP-75, JP-100	—	—

LIGHT DUTY PULLING GRIPS

Light Duty Pulling Grips are single weave construction made of a high grade galvanized steel strand. They feature a flexible eye for easy attachment to a pulling line.

Application

Light duty Pulling Grips are used in general underground electrical construction where pulling tensions are low. They are also used for wiring industrial plants and commercial buildings.



Cable Range	Part #	Description	Approx.* Breaking Strength	Length	
				Eye	Mesh
Short					
.50- .61	3303-001	LD-050S	2800	5	11
.62- .74	3303-002	LD-062S	2800	5	11
.75- .99	3303-003	LD-075S	4000	6	12
1.00-1.24	3303-004	LD-100S	5300	7	13
1.25-1.49	3303-005	LD-125S	5300	7	14
1.50-1.74	3303-006	LD-150S	6800	8	15
1.75-1.99	3303-007	LD-175S	8500	8	17
2.00-2.49	3303-008	LD-200S	8500	9	18
2.50-2.99	3303-009	LD-250S	10600	9	18
3.00-3.49	3303-010	LD-300S	14700	10	20
Standard					
.50- .61	3303-011	LD-050	2800	5	16
.62- .74	3303-012	LD-062	2800	5	16
.75- .99	3303-013	LD-075	4000	6	20
1.00-1.24	3303-014	LD-100	6800	7	20
1.25-1.49	3303-015	LD-125	6800	7	21
1.50-1.99	3303-016	LD-150	6800	8	23
2.00-2.49	3303-017	LD-200	8500	9	25
2.50-2.99	3303-018	LD-250	8500	9	27
3.00-3.49	3303-019	LD-300	10600	10	30
3.50-3.99	3303-020	LD-350	14700	10	32