

RCC-MK754ACM

REMOTE CONTROLLED GEAR-DRIVEN CABLE CUTTING TOOL

OPERATOR MANUAL



LINEMAN PROVEN

UTILITY APPROVED

SINCE 1976

WARNING To reduce the risk of injury, user must read and understand manual completely before first using this product and save this manual for future use

Huskie Tools is not affiliated with, authorized, or endorsed by Milwaukee Electric Tool Corporation. Milwaukee listed batteries and chargers are being re-sold by Huskie Tools. Milwaukee® M18™ REDLITHIUM™ are registered trademarks of Milwaukee Electric Tool Corporation. Huskie Tools is not affiliated with, authorized, or endorsed by Makita® Corporation. Makita® listed batteries and chargers are being re-sold by Huskie Tools. Makita® and LXT® are registered trademarks of Makita® Corporation.



**Huskie
TOOLS®**

**BUILT FOR EVERYTHING
THAT'S ON THE LINE.™**

HUSKIETOOLS.COM

PRE-USE CHECKLIST:

- Visually confirm there are no missing or broken components. If found, stop use and have the tool checked by a qualified technician.
- Please read the instructions supplied with the battery and charger.
- Check all tool functions prior to use.
- Please read all instructions prior to use.



**Thank you for purchasing
a Huskie Tools product.**

Our mission is to supply the finest cable connecting and cutting tools and cable-related products to the transmission and distribution markets. Huskie Tools products will represent state-of-the-art tools and be dependable and safe.

THE POWER TO CHOOSE.

TABLE OF CONTENTS

MODEL: RCC-MK754ACM

Description	4
Safety Symbols	5
Safety Information	6
Advisory: FCC RF Exposure Compliance	7
Operating Instructions	8-9
Troubleshooting Guide	10
Warranty Information	11

RCC-MK754ACM

The RCC-MK754ACM is a Gear-Driven Remote Cable Cutter.



WHAT'S INCLUDED

EACH TOOL KIT INCLUDES:

REMOTE CONTROL GEAR-DRIVE
CABLE CUTTER

RF REMOTE WITH 9V BATTERY

MAKITA LXT® LITHIUM-ION 5.0AH

MAKITA LXT® LITHIUM-ION 2.0AH

120VAC CHARGER

TRIPOD

GROUNDING STUD AND SCREW

[2] EYE BOLTS

TOOL CASE

SAFETY FEATURES

- Tool can only be used as a remote cutter; there is no trigger on tool
- Gear-Drive blade design ensures only the desired cable is cut
- Grounding Stud for extra safety should cable not be discharged—fits multiple clamp styles
- LED lights on tool for power, pairing and blade engagement for safe tool set up and operation
- Remote Operation increases safety
- Encrypted signal is uniquely paired with tool to prevent ability of powering a different tool
- Radio Frequency signal not affected by obstructions
- Two-button operations prevents inadvertent tool activation
- LED lights confirm complete cut ensuring safe operation methods

SPECIFICATIONS

CUTTING ESTIMATES (5.0Ah BATTERY)


1500 MCM ALUMINUM	125 Cycles/Charge
1000 MCM Copper	100 Cycles/Charge

CUTTING CAPACITIES

MAX O.D. CABLE	2 1/8"
----------------	--------

Huskie Tools is not affiliated with, authorized, or endorsed by Milwaukee Electric Tool Corporation. Milwaukee listed batteries and chargers are being re-sold by Huskie Tools. Milwaukee® M18™ REDLITHIUM™ are registered trademarks of Milwaukee Electric Tool Corporation. Huskie Tools is not affiliated with, authorized, or endorsed by Makita® Corporation. Makita® listed batteries and chargers are being re-sold by Huskie Tools. Makita® and LXT® are registered trademarks of Makita® Corporation.



SAFETY SYMBOLS


You will see this symbol  Exclamation-Triangle throughout this manual. The purpose of this symbol is to call your attention to hazards and/or unsafe practices that have the potential to cause injury or property damage. The severity of each hazard is further explained in detail below. Failure to follow all instructions may result in electric shock, fire and/or serious injury. The term “power tool” in all warnings refers to your battery operated (cordless) power tool.

 DANGER
Immediate hazards are present which will result in severe injury or death if not avoided.

 CAUTION
Hazards or unsafe practices may result in injury or property damage if not avoided.

 WARNING
Hazards are present that could result in severe injury or death if not avoided.

 WARNING	
	Read all instructions and safety information detailed in this operator manual prior to operating or servicing this tool. Failure to observe this warning could result in severe injury or death.

 DANGER	
	Electric Shock Hazard: Use appropriate personal protective equipment when using this unit on or near energized electrical lines.

 DANGER	
	Cutting Hazard: Remove battery before servicing. Keep hands away from cutting head during cycle.

 CAUTION	
	Wear Eye Protection: Use safety glasses when operating or servicing this tool to prevent eye injury from flying debris.



**DO NOT DISCARD
THIS PRODUCT OR
THROW AWAY!**

FOR RECYCLING INFORMATION,
CONTACT 800-822-8837

SAFETY INFORMATION

DANGER

WORK AREA SAFETY

- Keep work area clean and well lit. Cluttered or dark areas invite accidents.
- Do not operate power tools in explosive atmospheres, such as in the presence of flammable liquids, gases or dust. Power tools create sparks which may ignite the dust or fumes.
- Keep bystanders away while operating a power tool. Distractions can cause you to lose control.

CAUTION

PERSONAL SAFETY

- Stay alert, watch what you are doing and use common sense when operating a power tool. Do not use a power tool while you are tired or under the influence of drugs, alcohol or medication. A moment of distraction while operating power tools may result in personal injury.
- Use personal protection equipment. Always wear eye protection. Safety equipment such as dust mask, non-skid safety shoes, hard hat, or hearing protection used for appropriate conditions will reduce personal injuries.
- Do not overreach. Keep proper footing and balance at all times. This enables better control of the power tool in unexpected situations.

WARNING

TOOL USE AND CARE

- To prevent leakage, overheating, smoke generation, fire, and rupturing from occurring, follow these instructions when handling our rechargeable power tools (tool main body/battery pack/charger).
- Do not force the tool. Use the correct tool for your application. The correct tool will do the job better and safer at the rate for which it was designed.
- Do not use the tool if the switch does not turn it on and off. Any tool that cannot be controlled with the switch is dangerous and must be repaired.
- Disconnect the battery pack from the tool before making any adjustments, changing accessories, or storing. Such preventive safety measures reduce the risk of starting the tool accidentally.
- Store idle tools out of the reach of children and do not allow persons unfamiliar with the tool or these instructions to operate the tool. These tools can be dangerous in the hands of untrained users.
- Maintain tools. Check for misalignment or binding of moving parts, breakage of parts and any other condition that may affect the tools operation. If damaged, have the tool repaired before use.
- Use power tools only with specifically designated battery packs. Use of any other battery packs may create a risk of injury and fire.
- Under abusive conditions, liquid may be ejected from battery; avoid contact. If contact accidentally occurs, flush with water. If liquid contacts eyes, additionally seek medical help. Liquid ejected from the battery may cause irritation or burns.

Read the instructions supplied with the battery and charger.

ADVISORY: FCC RF EXPOSURE COMPLIANCE

The RCC-MK754AC tool and remote contain FCC ID: MCQ-XBEE3. IC: 1846A-XBEE3

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference and
2. This device must accept any interference received, including interference that may cause undesired operation.

PORTABLE DEVICE DESIGNED ONLY FOR OCCUPATIONAL USE

Caution: Device must be restricted to occupational use. See tool use instructions that follow for specific operating requirements. This advisory and its information is required for FCC RF exposure compliance.

Tool Use Instructions: How to use the device in order to ensure compliance with the occupational/controlled exposure limits.

Maintain hands and fingers a minimum distance of 20mm from the device antenna. Antenna shown.

Power ON remote - check device connection LED is on.

Hold Activation Buttons until the Blade Engaged LED turns out. Typical time required is 12-15 seconds.

Power OFF remote - before approaching the tool.



OPERATING INSTRUCTIONS

1. POSITION, RIG, AND GROUND

Secure the blade around the cable to be cut and make sure the blade engagement lever is secured. To secure the lever, pull down lever as shown and move blade into pinion gear. Release once blade stops.



If necessary, use the rigging points on the tool to secure it from falling after the cut is made. The tool has several options for rigging depending on application. The kit will include hanging rings for proper rigging.




Grounding stud is provided. Attach the stud to pivot bolt as shown and adjust angle to avoid interference with the cable. Lock the position of the stud in place by tightening the lock nut.



OPERATING INSTRUCTIONS (CONTINUED)

2. POWER ON

Once tool is secured and blade is engaged, press the power switch “ON”. the Green power LED and Yellow blade engage LED will illuminate. Then press the “CUT” switch. The tool automatically goes to the “OPEN” position each time it is powered up for safety.



Once the hand held remote is powered on, the blue “paired” LED will illuminate.

Be sure to check battery levels on both the tool and remote before operating.

Blade engage (yellow) and Pairing (blue) LED lights

3. OPERATE

At this point, operator can safely remove themselves from the area or line of sight with the tool for actual operation. This will be up to each company for their own policy and procedures for remote cutting.

On the remote hand-held device, turn power switch to “ON” position. Confirm “power”, “blade engage” and “paired” LED’s are all illuminated.

To operate the tool to cut, press both buttons on the remote - no sequence is needed, as long as both buttons are pressed, the tool will operate. The tool will stop when one or both buttons are released.



DEVICE PAIRED (BLUE)

BATTERY LOW (RED)

BLADE ENGAGED (YELLOW)



The operator will know the cable is cut when the yellow “blade engaged” LED is off - this indicates the blade has completely gone through its arc and out the other side, leaving no chance the cable has not been cut. If LED is still illuminated, the blade has stopped, and cable is not cut. Cycle time should be approximately 15 to 20 seconds.

TROUBLESHOOTING GUIDE

BEFORE YOU BEGIN

1. Make sure that the battery is charged. Recheck the battery after several minutes to make sure the battery is holding its charge.
2. Use a nonflammable contact cleaner or pencil eraser to clean the electrical contacts on the battery and tool.
3. Reinstall the battery and check the tool again.

REC-MK754M		
PROBLEM	CAUSE	SOLUTION
Motor runs but the tool jaws will not advance	Insufficient hydraulic oil	Consult factory for repair service
	Air block in hydraulic system	Invert tool to allow air to rise towards the top of the oil bladder
	Defective hydraulic circuit	Consult factory for repair service
Motor runs, tool jaws advance, but will not build pressure	Insufficient hydraulic oil	Consult factory for repair service
	Defective suction valve or bypass cartridge	Consult factory for repair service
Motor will not run at all	Defective battery	Charge or replace battery
	Bad contact or loose battery connections	Check all connections and wires
	Misaligned switch	Check to make sure that switch is properly aligned with trigger
Consult factory for repair service		
Tool jaws will not release	Tool did not complete a full cycle and bypass	Press trigger and allow tool to bypass, then release tool jaws
	Connector is jammed in tool jaws	Press and hold release trigger while prying tool jaws apart
	Release trigger is bent or misaligned	Consult factory for repair service

WARRANTY INFORMATION

SL-SERIES BATTERY OPERATED PRODUCTS	5 YEARS
REC-SERIES BATTERY OPERATED PRODUCTS	5 YEARS
IL-SERIES BATTERY OPERATED PRODUCTS	3 YEARS
ECO-SERIES BATTERY OPERATED PRODUCTS	1 YEAR

BATTERIES

BL1820B, BL1850B

3 YEARS

CHARGERS

DC18SE, DC18RC

3 YEARS

The warranty does not cover any damages incurred from a Huskie tool including damages to property, bodily injuries and lost wages resulting from such injuries. This warranty solely covers the repair or replacement of tools supplied by Huskie. These remedies are exclusive, and the total liability of Huskie Tools, LLC whether based on contract, warranty, negligence, indemnification, strict liability or otherwise, shall not exceed the purchase price of the tool. In no event, shall Huskie Tools, LLC be liable for consequential, incidental or special damages.

HUSKIE TOOLS, LLC MAKES NO OTHER WARRANTIES OF ANY KIND, EXPRESSED OR IMPLIED, AND ALL IMPLIED WARRANTIES INCLUDING ANY WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

Huskie reserves the right to determine all warranty claims. Huskie will not warranty tools containing parts or batteries not originally supplied by Huskie. Failure due to misuse, improper maintenance, misapplication, not following instructions or warnings, abuse or repairs attempted by anyone other than Huskie Tools, LLC, or an authorized service center renders this warranty null and void.

REPAIR AND WARRANTY CLAIMS

All claims must be sent to Huskie for inspection and authorization. A Return Goods Authorization (RGA) is required before shipping tools to Huskie. Secure the authorization by telephoning or writing to Huskie's main office with details of the claim. Non-warranty repairs are handled using the same procedure. Repairs exceeding 50 percent of the cost of a new tool will be advised before repairs are made.



**Huskie
TOOLS®**

**2105 W. CORPORATE DR STE B
ADDISON, IL 60101-1470**

**PHONE 800-860-6170
FAX 800-345-3767**

HUSKIETOOLS.COM

Huskie Tools reserves the right to change this information without further notice and holds no liability for printing errors in this content.

Copyright © 2021 Huskie Tools, Inc. All Rights Reserved.