



HUSKIE TOOLS POWER GRIPS™

CABLE GRIPS CROSS REFERENCE CHART

This chart is intended to help you easily find the HUSKIE TOOLS grip model that most closely matches other brands models. These comparisons are the closest available but There may be variations in specifications between brands.

It's important that you check your required specifications to ensure that the grip you select is correct for your application. If you have any questions, contact us @ info@huskietools.com

Wire Pulling Grip Cross Reference				
HUSKIE TOOLS	Capacity	Range	KLEIN	LITTLE MULE
For Bare Aluminum, AAC, ACSR, ACSS, Copper Cable *Guy strand				
TG30	3000	.19"-.87"		
*TG45	5000	.19"-.87"	KT4500, KT4650, 1656-20, 1656-30 (8000lbs->)1656-40, 1656-50 / KT4600	LMG4500 LMG4600 (10,000 lbs)
TG45M	5000	.19"-1.1"	KT4650, KT4500, , 1656-20, 1656-30 8000lbs->)1656-40, 1656-50 1656-60/KT460	LMG4500 LMG4600 (10,000 lbs)
*TG46	8000	.19"-.87"	KT4500, KT4650, 1656-20, 1656-30 (8000lbs->)1656-40, 1656-50 / KT4600	LMG4600 LMG4500
TG48	9000	.68"-1.4"	, 1656-50, 1656-60, 1678-20 1678-30, 1678-40, 1678-50, /KT4800	LMG4800
TG47	13000	.7"-1.4"	1628-30	LMG4700
TG49	15000	1.2"-1.8"	1628-40, 1628-50	LMG4900
Hot-Line Grip Spring Loaded Latch, Notched Handle (locking)				
TG451R	5000	.19"-.87"	KT4501, 1656-20H, 1656-30H KT4601, 1656-40H , 1656-50H	LMG4501 LMG4601
TG461R	8000	.19"-.87"	KT4501H, 1656-20H, 1656-30H KT4601, 1656-40H , 1656-50H	LMG4501 LMG4601
TG481R	8000	.68"-1.4"	KT4801 , 1656-50H, 1656-60H,	LMG4801
For Copper Cable, Covered Cable, Tree Cable, Guy Strand				
*TG25	2200	.12"-.5"	1613-30, 1613-40(4500lbs)	
TG45C	5000	.19"-.87"	1685-20, 1611-20, 1611-30, 1659-20 1659-30, 1656-20, 1656-30	
TG48CL	9000	.68"-1.4"	1685-31, 1611-50, 1659-50, 1656-50, 1656-60	
For Steel Strand, Guy Strand , Tree Cable, *EHS, Messenger, Wire Rope				
*IG20	2200	.1"-.59"	1613-30, 1613-40, 1604-20 (5000lbs)	LMG2000
TG45A	5000	.19"-.87"	1684-74, 1625-20, 1625-20-7/8	LMG4500A
TG46A	8000	.19"-.87"	1684-74, 1625-20, 1625-20-7/8, 1684-5, 1692-5	LMG4500A LMG4600A
TG50A	9000	.31"-1.1"	1628-16, 1628-17, 1628-18	