



3 Function Shower Rail

Nero



Versions:202401

Drawing



Specifications

Watermark License
WM-060093
Temperature Rating
Min 1°C-Max 75°C
Pressure Rating
Min 150kpa - Max 500kpa

Packaging Includes

1x Hand Shower (Built- In Check Valve)
1x Shower Rail
1x 1.5m PVC Hose
2x Back Plates

Finish & SKU

- | | | |
|---|--|--|
|  Chrome
NR314CH |  Gun Metal
NR314GM |  Brushed Nickel
NR314BN |
|  Matte Black
NR314MB |  Brushed Gold
NR314BG | |






*Dimensions are nominal measurements only.

Nero

Important

All products must be installed by licensed plumbers.

All pipework must be thoroughly flushed prior to installation, as foreign materials may block the flow regulating device and reduce the flow of water.

 1. Drill a $\phi 6$mm hole at the downwards outlet vertical downward position in the recomendation range.	 2. Screw the adapter onto the outlet. Push wall plug into drilled hole. Fit lower mounting pillar in place with screw. Tighten firmly.	 3. Slide both top and bottom back plate onto the rail assembly, as shown on the picture.
 4. Push shower rail assembly onto the wall/tile face. Tighten grub screws firmly. Slide the back plates against the wall/tile face properly.	 5. Connect shower rail and hand shower with hose. TEST & CHECK FOR LEAKS.	

Nero

info@nerotapware.com.au
nerotapware.com.au

11-13 Buontempo Road
Carrum Downs Vic 3201

