

Toilet Colour Flush Buttons + Seat Hinge Covers

Colour toilet flush buttons and seat hinge covers to complement your bathroom theme.

Available for selected toilet suites including Arko, Modia, Limni and Syros.

Easy to install.



Brushed Nickel



Gunmetal



Brushed Gold



Brushed Bronze



Black Matte



White Matte



Colour flush buttons

Note: Toilets come with chrome flush buttons and stainless steel seat hinges covers as standard.

Colour buttons and seat hinge covers are extras, fitted in place of the standard items.



Colour seat hinge covers – Set of 2



Wall faced toilets



Floor mount toilets



Wall hung toilets

Order codes

COLOUR FLUSH BUTTONS



Colour Flush Buttons

Colour	Order code
Brushed Nickel Fl/btn	191212
Gunmetal Fl/btn	191206
Brushed Gold Fl/btn	191226
Br Bronze Fl/btn	194514
Black Matte Fl/btn	191201
White Matte Fl/btn	192413

COLOUR SEAT HINGE COVERS



Seat Hinge Covers to suit Deluxe/Classic seat

Colour	Order code
Br Nickel Hinges-Dlx-Seat	191236
Gunmetal Hinges-Dlx-Seat	191235
Br Gold Hinges-Dlx-Seat	191233
Br Bronze Hinges-Dlx-Seat	19
Black Hinges-Dlx-Seat	191234
White Hinges-Dlx-Seat	192414



Seat Hinge Covers to suit Slim toilet seat

Colour	Order code
Br Nickel Hinges-Slim-Seat	191216
Gunmetal Hinges-Slim-Seat	191210
Br Gold Hinges-Slim-Seat	191230
Br Bronze Hinges-Slim-Seat	193418
Black Hinges-Slim-Seat	191232
White Hinges-Slim-Seat	192360



Seat Hinge Covers to suit Flat toilet seat

Colour	Order code
Br Nickel Hinges-Flat-Seat	191215
Gunmetal Hinges-Flat-Seat	191209
Br Gold Hinges-Flat-Seat	191229
Br Bronze Hinges-Flat-Seat	19
Black Hinges-Flat-Seat	191231
White Hinges-Flat-Seat	192360

SEIMA

kitchen + laundry + bathroom ware

seima.com.au

Please note

- Installation shall be in accordance with AS/NZS3500.
- All measurements are in millimetres. Height dimensions are to base of pan. Make allowance for bedding.
- Bedding: Pan may be bedded with cement base or using silicone sealant. Fix pan to floor using a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast-drying cement.

- Bracket fixing: The pan should be bedded with silicone sealant and fixed with the brackets supplied.
- Do NOT use epoxy type adhesives.
- Dimensions are nominal and subject to normal ceramic manufacturing variations.
- Specifications may vary without notice as part of our continuous improvement practices.
- Clean with a damp cloth. Do not use abrasive cleaners, liquids or pastes.