

MODEL 020942

## ASSEMBLY AND DRESSING INSTRUCTIONS

Blending innovative design, cutting-edge technology and the grace and elegance of traditional crystal, ALLEGRI® proudly brings you a new approach to lighting. ALLEGRI® fixtures are made from the finest raw materials and are brought to life through a combination of traditional manufacturing, such as sand casting, hand-forging and technology driven techniques including laser cutting.

Enclosed are detailed instructions on how to properly install your fixture. Please read all instructions carefully. If you need further assistance, please contact the dealer from which you purchased this product or call 866-820-2665 to speak with an ALLEGRI® customer service representative. We hope you enjoy your fixture!

## **WARNING!** **CONTENTS ARE FRAGILE** **HANDLE WITH CARE**

**THE METAL FRAME, FINISH AND CRYSTAL COMPONENTS OF THIS CHANDELIER ARE VERY DELICATE.**  
**PLEASE EXERCISE EXTREME CAUTION DURING UNPACKING AND INSTALLATION.**

**PLACE ALL PIECES TOGETHER IN A NUMERICAL ORDER AND IN THE ORIENTATION DEPICTED.**  
**REFER TO THE PARTS LIST TO AVOID ANY CONFUSION BETWEEN PARTS THE PARTS NUMBER MUST COINCIDE.**

**CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY AND PROPERTY DAMAGE. All electrical components must be installed only by a Licensed Electrician.**

This product must be installed in accordance with the National Electric Code (NEC), and appropriate local electrical code(s), by a person familiar with the construction and operation of the product and the hazard involved.\*

**CAUTION: Do not exceed maximum wattage note on fixture. Uses only recommended bulbs with fixture.**

### **GENERAL NOTES**

- ❖ For your safety and proper operation of fixture, read and understand all instructions completely before commencing installation.
- ❖ This fixture is suited for dry locations. Never install fixture on damp ceiling; room should be dry and well ventilated.
- ❖ Extreme care should be taken to avoid damage to the surface of lighting fixture and wires. Wearing gloves is recommended for installation.
- ❖ Connect ribbed wire of lighting fixture to live wire, while smooth wire of lighting to neutral. Connect bare copper or silver color ground wire of fixture to the double colored or green wire of outlet box.
- ❖ Use UL LISTED wire nuts for the wiring connections in this fixture. Wrap wire nut connections with UL LISTED electrical tape.
- ❖ Keep lighting away from acid, alkali and other corrosive chemical or gas; clean the fixture with a clean cloth only.
- ❖ Fixture must be firmly secured when installing ceiling tube, chain pipe and other connecting parts.
- ❖ Never cover the lighting fixture when power is connected.
- ❖ Disconnect the power before installing, cleaning and/or replacing light bulb.
- ❖ Extreme care should be taken when installing and cleaning of Glass and/or Crystal Components.
- ❖ This product is rated 110-130V/60HZ bulb 40W Maximum.
- ❖ Save these instructions for future reference.

### **WARNING**

The electricity must be turned off at the main fuse box or circuit breaker before installing this fixture. Turning the power off using the light switch may not be sufficient to prevent electrical shock.



\*ALLEGRI will not be liable for injury or damage caused by improper installation, lamping or use of this fixture.



# ALLEGRI.

BY KALCO LIGHTING™ CANOPY MOUNTING INSTRUCTION

MODEL 020941



All electrical components must be installed by a licensed electrician in accordance with the National Electric code and the appropriate local electrical codes.



#### MOUNT FLUSH FIXTURE AS FOLLOWS:

1-Place cross bar 6 temporarily on the Outlet Box 3 with screws 7 and mark all four slots #2 on the ceiling then remove cross bar and install four anchors for screws on the ceiling in the four spots previously marked, then install Cross bar with two Outlet Box screws 7 and place screws 5 in the four anchors.

2-Raise Flush Plate 8 close to ceiling and connect wires as follows: Connect fixture ribbed wire to power suply black wire and fixture smooth wire to power supply white wire. Connect fixture bare copper or silver bare wire to power supply green wire.

3-Secure wire connections with plastic wire nuts and electricians black tape or as required by your local electric code. Carefully tuck excess of wire inside outlet box.

4-Align Flush Plate four holes to cross bar four Studs 4 and rise flat to ceiling, (make sure sure wires does not get pinched between fixture flush plate and outlet box). Secure frame with Chrome hex nuts 9 and chrome decorative nuts 10.

Proceed to assemble frame as shown in page 4.




# ALLEGRI.

BY KALCO LIGHTING™

## FRAME ASSEMBLY INSTRUCTIONS

MODEL 020942



### FRAME ASSEMBLY:

1-Screw center stem 11 to center connector on flush plate make sure stopper 11 stays on bottom side of stem.

2-Place acrylic disc 12 to center stem 11 and secure it with connector 13, then connect Threaded rod 14 to connector 13.

3-Place crystal bobeche to threaded rod and place washer 16 under bobeche. Secure all parts by screwing finial 17 at the bottom.

4-Install all light bulbs, please use 40w candelabra bulbs (Krypton type recommended).

5-Turn switch ON for test, then turn it OFF and proceed to install crystal set as shown in page 5.





# ALLEGRI.


BY KALCO LIGHTING™

## CRYSTAL DRESSING INSTRUCTION


MODEL 020942




All electrical components must be installed by a licensed electrician in accordance with the National Electric code and the appropriate local electrical codes.



Code	Qty
A	210
B	96
C	48
D	1



A - 1502 ø10mm 10pcs



B

1080 24# 3pcs

1080 22# 2pcs

1080 20# 1pcs

1080 18# 2pcs

1080 16# 1pcs

1080 14# 2pcs

C

1080 28# 1pcs

1080 26# 1pcs

1080 24# 1pcs

1080 22# 1pcs

1080 20# 1pcs

1080 18# 1pcs

1080 16# 1pcs

1080 14# 1pcs

1080 12# 2pcs

### CRYSTAL TRIMMING:

1-Crystals (A) comes factory assembled

2-Install 96 crystal strands (B), attach the thicker side of crystal strand to top ring first, when all 96 are done then attach the thinner side of crystal strand to the middle Ring

3-Install 48 crystal strands (C), attach the thicker side of crystal strand to middle ring first, when all 48 are done then attach the thinner side of crystal strand to the bottom Acrylic Disc

3-Install crystal ball (D) to the bottom finial 17.

Every ALLEGRI® fixture is of heirloom quality and will last for generations. To ensure it retains its brilliance and splendor for years to come, proper care and regular cleaning are necessary.

It is recommended that ALLEGRI® fixture, and particularly their crystal trim, be lightly dusted with a feather or lambs wool duster, or soft brush every two months, or whenever it appears dull or dusty. A thorough cleaning should be completed every six months.

---

Before cleaning an ALLEGRI® fixture, first locate the fixture's trim diagram. This will assist in replacing the crystal trim in its proper location after cleaning. Should a replacement trim diagram be required, please call 866-820-2665 to speak with an ALLEGRI® customer service representative, who can provide a new diagram.

ALLEGRI® recommends several different cleaning methods, depending on the type of fixture. Some fixtures can be cleaned with limited removal of crystal, while others must be completely untrimmed.

Place a soft towel or blanket directly beneath the fixture to limit the damage to both the crystal and the surface below the fixture, should a piece of crystal be dislodged during the cleaning process. Extreme care must be taken around any electrical fixture. For personal safety and the safety of the fixture, be sure that the fixture has been turned off. Never rotate or spin the fixture as this can cause the fixture to lose support and fall. Instead, move around the fixture while cleaning.

---

#### White Glove Method

Prepare a cleaning solution of one part isopropyl alcohol to three parts distilled water and place in a clean spray bottle.

Do not use packaged cleaning fluids, as many of these contain ammonia, which may degrade the finish of the fixture and the quality of the crystal.

Wearing white cotton gloves, spray one glove with the solution and keep one dry. Gently polish each crystal with the damp glove and immediately wipe it with the dry glove. Do not tug or pull on the crystal, as this may cause the connectors to chip or crack the crystal, or dislodge it from the fixture.

Warning: To reduce the risk of personal injury due to fire and/or electric shock, never spray solution at or near the fixture.

---

#### Crystal Removal Method

Gently remove trim and hand-wash the crystal in lukewarm water using a mild detergent. Rinse in clean water and dry with a soft clean cloth. Do not soak finished crystal such as SWAROVSKI ELEMENTS Colors: Teak, Golden Shadow or Silver Shade, for extended periods, as this may degrade the crystal's finish.

With the fixture untrimmed and turned off, wipe the frame, including the light bulbs once they are completely cool, with a soft cloth.

Wearing white gloves, finger-cots or using a soft clean cloth, gently replace the trim as directed in the trim diagram.