



FIXTURE ASSEMBLY:


1. Unpack fixture carefully, note fixture frame comes fully assembled and two sets of hands are needed for installation.
2. Prepare (4) Anchor screw, pre-mount onto concrete ceiling through crossbar hole.
3. Take out part#3#, 5#, 6# from box, then pass S/S cable & wire from 5#, 6# through part3#, connected to driver and tuck the wires with orange wire cap;
- Note: Please connect wires according to + and - labels.
4. Use anchor screw to fix part#1 onto the concrete ceiling.
5. Connect the main wire with the power supply circuit see wire connection diagram.
6. Use part#4 to fix part#3 onto part#1.
- ?Use part#2 to fix part#? onto part#1.
8. Clean fixture with a damp microfiber or cotton cloth, avoid using any cleaners that contains chemicals or abrasives that would damage fixture finish.



Weight of whole fixture 36KG



(FRONT VIEW)



NOTE:

To prevent water entering the fixture, the grub screws must be tightened such that the frame is pressed tightly to the water-proof washer.

WARNING:

- 1.If you are unfamiliar with electrical wiring,call a qualified electrician to install this unit. More than one person may be necessary to install this fixture,make sure you have enough qualified help.
- 2.Turn off the power to the fixture's circuit at the service panel.Use a voltage detector to verify that the power is off.



Every ALLEGRI® fixture is of heirloom quality and will last for generations. To ensure it retains its brilliance and splendor for years to come, proper care and regular cleaning are necessary. It is recommended that ALLEGRI® fixture, and particularly their crystal trim, be lightly dusted with a feather or lambs wool duster, or soft brush every two months, or whenever it appears dull or dusty. A thorough cleaning should be completed every six months.

Before cleaning an ALLEGRI® fixture, first locate the fixture's trim diagram. This will assist in replacing the crystal trim in its proper location after cleaning. Should a replacement trim diagram be required, please call 800-525-2655 to speak with an ALLEGRI® customer service representative, who can provide a new diagram.

ALLEGRI® recommends several different cleaning methods, depending on the type of fixture. Some fixtures can be cleaned with limited removal of crystal, while others must be completely untrimmed.

Place a soft towel or blanket directly beneath the fixture to limit the damage to both the crystal and the surface below the fixture, should a piece of crystal be dislodged during the cleaning process. Extreme care must be taken around any electrical fixture. For personal safety and the safety of the fixture, be sure that the fixture has been turned off. Never rotate or spin the fixture as this can cause the fixture to lose support and fall. Instead, move around the fixture while cleaning.

White Glove Method

Prepare a cleaning solution of one part isopropyl alcohol to three parts distilled water and place in a clean spray bottle. Do not use packaged cleaning fluids, as many of these contain ammonia, which may degrade the finish of the fixture and the quality of the crystal.

Wearing white cotton gloves, spray one glove with the solution and keep one dry. Gently polish each crystal with the damp glove and immediately wipe it with the dry glove. Do not tug or pull on the crystal, as this may cause the connectors to chip or crack the crystal, or dislodge it from the fixture.

Warning:

To reduce the risk of personal injury due to fire and/or electric shock, never spray solution at or near the fixture.

Crystal Removal Method

Gently remove trim and hand-wash the crystal in lukewarm water using a mild detergent. Rinse in clean water and dry with a soft clean cloth. With the fixture untrimmed and turned off, wipe the frame, including the light bulbs once they are completely cool, with a soft cloth. Wearing white gloves, finger-cots or using a soft clean cloth, gently replace the trim as directed in the trim diagram.