SPECIFICATION SHEET

MAGNET SHEETING WITH MATTE WHITE VINYL

FEATURES AND ADVANTAGES:

- Matte white vinyl bonded to magnet sheeting, is compatible for Solvent, UV curable and UV screen printing.
- Magnet sheeting is attracted to iron, easy to apply, remove and change, without leaving any residue.
- Will not demagnetize, anti-rust

CONSTRUCTION DRAWING:



→ matte white vinyl: 4mil(100μm)

→ magnet sheeting: different thickness

PACKAGING:



3" core



lid-tray

PROCESS AND STORAGE:

- Working condition: temperature 15°C/59°F to 30°C/86°F, and relative humidity 30% to 60%.
- Application condition: temperature change is within 40°C/104°F daily.
- Storage condition: closed preserve avoiding sunlight, in temperature 10°C/50°F to 35°C/95°F, relative humidity 20% to 70%
- Shelf life: 12 months under normal storage conditions. Unfinished material should be re-packed, and used up within a month.

PRINTING INDEX:

- ✔ Compatible with Solvent inks
- ✔ Compatible with Eco-Solvent inks
- ✔ Compatible with UV-Curable inks
- ✔ Compatible with Latex inks

LARGE-FORMAT PRINTING GUIDELINES:

Precautions must be made when using MegaMag with large-format printers. MegaMag has been fully tested with the PrismJET 54Gen2 eco-solvent printer.

PrismJET 54Gen2 Magnetic Printing Guide
Click here to view detailed printing instructions (PDF)

SPECIFICATION DATA:

PART NO.	MAGNET THICKNESS (MIL/INCH)	TOTAL THICKNESS (MIL/INCH)
MEM-MM-24X24X50	20-mil / .020inch	24-mil / 0.24-inch
MEM-MM-24X40X50	20-mil / .020inch	24-mil / 0.24-inch
MEM-MM-24X48X50	20-mil / .020inch	24-mil / 0.24-inch