

DEF/UTILITY PUMPS

Use in a variety of applications, including agriculture, construction, and automotive.



LEGACY OF RETAIL
FUEL TRANSFER SOLUTIONS

DO8TS-115PO

8 GPM | 30 L/min

115VAC
Voltage (Power Source)

DO8TS-012PO

8 GPM | 30 L/min

12V DC
Voltage (Power Source)



Compatible with Diesel Exhaust Fluid (DEF), Antifreeze, Windshield Wash Fluid, Ammonium Sulfate, Non-Potable Water, and other water-based chemicals.



Item# 180000-01 shown

The GPI DEF/Utility Pumps offer
THE BEST VALUE
for fluid transfer from bulk containers.

The GPI DEF/Utility pump is designed to do more!

It's the perfect solution for dispensing from IBC totes and drums and conveniently works as a direct bolt-on replacement for many DEF tote systems. With a flow rate of 8 GPM, this pump is used to move anti-freeze, windshield wash fluid, and other water-based chemicals.

POWER SUPPLY OPTIONS

115V (AC) for stationary applications and 12V (DC) for mobile applications

SELF-PRIMING

Self-priming utility pump for clean fluids

EASY INSTALLATION

Features foot mount with standard 100mm x 80mm bolt pattern for simple installation on tote brackets or custom mounting options

AUTO SHUT-OFF

Motor protected by run timer to prevent accidental continuous operation

REPLACE YOUR PUMP

- Direct bolt-on replacement for many DEF tote systems



GREAT PLAINS INDUSTRIES



DEF/UTILITY PUMPS

Use in a variety of applications, including agriculture, construction, and automotive.



LEGACY OF RETAIL
FUEL TRANSFER SOLUTIONS

D08TS-115PO

Part No.:	180000-01
Voltage, Input:	115V (AC) 50/60 Hz
Motor RPMs:	1750
Motor HP:	0.50
Amps (Rated):	1.3
Power Cord:	4.5 ft. (1.4 m), 18AWGx3C, Factory-Installed



SPECS (ALL MODELS)

Max. Flow Rate:	8 GPM 30 L/min
Type:	Oscillating Diaphragm
Duty Cycle:	20 min.
Max. Discharge Pressure:	Up to 23 PSI (1.6 bar)
Suction Lift:	Up to 9 ft. (2.75 m)
Operating Temperature:	23° F to 104° F (-5° C to 40° C)
Wetted Materials:	Nylon TPU EPDM Stainless Steel
Inlet:	3/4 in. Hose Barb
Outlet:	3/4 in. Hose Barb
Warranty:	Two-Year Pump

Refer to product owner's manual for
installation and safety instructions.

D08TS-012PO

Part No.:	180002-01
Voltage, Input:	12V (DC)
Motor RPMs:	1750
Motor HP:	0.24
Amps (Rated):	14.8
Power Cord:	4.5 ft. (1.4 m), 14AWGx2C, Factory-Installed



FLUIDS

For use with Diesel Exhaust Fluid (DEF), Antifreeze, Windshield Wash Fluid, Ammonium Sulfate, Non-Potable Water, and other water-based chemicals. See wetted materials list. **Not compatible with petroleum-based liquids.**
DO NOT USE WITH FLAMMABLE LIQUIDS.



See Model Specs
on Data Sheet

