

P-200 PA-200

Lightweight Oil Transfer Pumps for
thin to medium viscosity petroleum
fluids and up to 30W oil



LEGACY OF RETAIL
FUEL TRANSFER SOLUTIONS

8 | 30
GPM | L/min

12V DC/115 AC
Voltage (Power Source)



Our most versatile

LIGHTWEIGHT OIL PUMPS

The GPI Lightweight Oil Transfer Pumps are engineered to deliver flow rates up to 8 GPM (30 L/min) for use with non-flammable oil-based solvents. Designed specifically for thin to medium viscosity petroleum fluids and up to 30W oil. Modeled to move easily between barrels or drums.

SMART DESIGN

Lightweight design and spin collar inlet fitting makes moving between barrels and drums easy

LONG LIFE

Heavy-duty rotary gear design

VERSATILE

12V DC and 115V AC models available

INCLUDED ACCESSORIES

Ball valve nozzle
Dispensing hose
Telescoping Suction Pipe
Factory installed power cord

The
PERFECT
garage
companion!

*One oil pump that
transitions easily between
barrels or drums.*



GREAT PLAINS INDUSTRIES



P-200 PA-200

Lightweight Oil Transfer Pumps for thin to medium viscosity petroleum fluids and up to 30W oil



LEGACY OF RETAIL
FUEL TRANSFER SOLUTIONS



Part No.	Model
118000-9	P-200-2UR
Flow Rate:	8 GPM (30 L/min)
Voltage:	12V DC
Current Draw:	25 amps
Motor:	3250 RPM, 1/4 HP
Power Cord:	15 ft. (4.6 m), 12 AWG
Max Viscosity:	450 CPS

Part No.	Model
118003-11	PA-200-2UR
Flow Rate:	8 GPM (30 L/min)
Voltage:	115V AC
Current Draw:	3 amps
Motor:	3250 RPM, 1/4 HP
Power Cord:	3 ft (.91 m), 18/3 AWG with grounded plug
Max Viscosity:	450 CPS

FLUIDS⁺

Oil, up to 30W | Thin to medium viscosity petroleum fluids, up to 450 cp | Anti-Freeze | Non-flammable oil-based solvents
Do not use with gasoline, diesel fuel or waste oil.

⁺See fluid compatibility of each pump model

SPECS (ALL MODELS)

Pump Technology:	Gear
Duty Cycle:	30 min. on / 30 min. off
Max Discharge Pressure:	Up to 16 PSI (1.10 bar)
Operating Temperature:	-20°F to 120°F (-29°C to 50°C)

Suction Pipe:	Telescoping 15 to 40 in MNPT
Pump Housing:	Polypropylene
Dispensing Hose:	12 ft. (3.7 m) x 1 in.
Warranty:	Two-Year Pump Warranty

Refer to manual for wiring instructions

