

# V35

Next-Generation High-Flow Pump  
for stationary applications fueling large equipment

# GPRO®

PROFESSIONAL GRADE  
PERFORMANCE



**132** | **35**  
l/min | GPM

**120V/240VCA**  
Doble voltaje configurable

## Your New Standard for **35 GPM Performance**

The GPRO V35 is engineered for professionals who demand fast, reliable, heavy-duty fueling. With a high-flow rate of 132 L/min, this pump handles large-volume transfers with ease. It features corrosion-resistant materials, a weatherproof sealed design, and two outlet fitting options for flexible, secure installation. Designed with quick access to the fuel strainer and field-replaceable components, the V35 helps reduce downtime and streamline maintenance—so your operations keep moving.

## HIGHEST TOTAL VALUE

### QUALITY

Built to withstand tough applications, backed by a limited lifetime warranty.

### DURABILITY

Weatherproof aluminum motor enclosure. Corrosion-resistant, powder coated cast iron pump.

### RELIABILITY

The Thermally Protected Motor prevents overheating for safe, reliable operation in demanding conditions.

### EASY MAINTENANCE

Quick access to the strainer and field-replaceable components, the V35 helps reduce downtime and extend service life — keeping operations moving.

### EASY INSTALLATION

Included tank adapter allows easy install and includes integrated port for vacuum breaker kit.

### SUPERIOR DESIGN

Leak-free O-ring fittings. Integrated check valve to keep the pump primed.

GREATER  
SUCTION  
LIFT than  
the competition:



**5.5m** of Gasoline  
**4.5m** of Diesel

### HIGH-PRESSURE PERFORMANCE

ideal for use  
with a hose  
reel, better  
performance  
with filters and  
accessories.



GREAT PLAINS INDUSTRIES



# V35

Next-Generation High-Flow Pump  
for stationary applications fueling large equipment

# GPRO®

PROFESSIONAL GRADE  
PERFORMANCE

The QM40 Fuel Meter  
mounts securely with  
the Quick-Fit 90-Degree  
Meter Adapter.

Available separately or  
included with the pump  
and meter combo.  
Filter kit sold separately.



V35+QM40 Pump and Meter Combo shown.  
Filter kit sold separately.

## HIGH-FLOW PERFORMANCE

### ADDITIONAL FEATURES:

- What you demand - professional grade fueling at 132 L/min for heavy-duty equipment.
- Delivers a corrosion-resistant fuel transfer pump that stands up to harsh environments and Mother Nature - weatherproof tested.
- Withstands the daily abuse of job-site handling.
- Quick-fit modular design for accessories to best suit pump footprint.
- Field replaceable switch and capacitor without compromising weather resistance or agency approvals.
- Easy access to fuel strainer: five minutes to clean strainer without removing the pump from the tank.
- Overhaul kits and replacement parts available to extend the service life of the pump.
- Extreme Temperature (XT) models are capable of operation in temperatures as low as -40°F (-40°C).
- Dual voltage configurable (120V/240V)

### SPECS (ALL MODELS)

|                                    |                 |                                                                |
|------------------------------------|-----------------|----------------------------------------------------------------|
| Max. Flow Rate:                    |                 | 132 L/min   35 GPM                                             |
| Voltage, Input:                    |                 | 120V (AC) 60Hz,<br>240V (AC) 60Hz<br>Dual Voltage Configurable |
| Pump Technology:                   |                 | Sliding Vane                                                   |
| Motor HP:                          |                 | 1                                                              |
| Max Discharge Pressure:            |                 | Up to 1.6 bar (23 PSI)                                         |
| Suction Pipe:                      |                 | Not Included                                                   |
| At Sea Level<br>70° F<br>(21.1° C) | Suction Lift:   | Up to 4.5m (15 ft.)                                            |
|                                    | Discharge Lift: | Up to 5.5 m (18 ft.)                                           |
| Pump Housing:                      |                 | Powder Coated Cast Iron & Aluminum                             |
| Warranty:                          |                 | Limited Lifetime Warranty                                      |

Refer to manual for wiring instructions



See Model Specs  
on Data Sheet

