

LM SERIES ELECTRONIC FLOW METER



The **FLOMEC® LM51DN Positive Displacement Flow Meter** has a modular design, and is low cost, lightweight and rugged, making it the best choice for overhead reel systems. Perfect for metering engine oils or transmission fluids with a maximum viscosity of 1,000 cp.

The electronic register module contains a microprocessor board powered by a lithium battery. It can be programmed to measure in pints, quarts, litres, or US gallons. The flow meter calibration factor is determined during factory test. The flow meter can be recalibrated in the field for fluids or different viscosity if required. A 6-digit liquid crystal display, accurate to the second decimal place, shows the exact amount of fluid dispensed. The entire register module is protected from the wear and tear of normal shop use by a rugged, glass filled, shock resistant, nylon housing.

SPECIFICATIONS

Technology:		Oval gear
Line Size:		½" NPT (Female)
Accuracy (% of Reading):		± 0.5%
Material Housing:	Housing:	Corrosion-Resistant Aluminum
	Oval Gears:	Vectra (LCP-plastic)
	O-Ring:	Viton
Flow Range:		0.25-8 GPM (1-30 L/min)
Pressure Rating:		5-1500 psi (0.35-103 bar)
Operating Temperature:		-4°F to +140°F (-20°C to +60°C)

APPLICATIONS (Typical application but not limited to)

- Motor Oils (SAE 5-50)
- Windshield Wiper Fluid
- Brake Fluid
- Engine Coolant Solutions
- Gear Oils (SAE 80-240)
- Antifreeze (Ethylene Glycol)
- Automatic Transmission Fluid

APPROVALS / WARRANTY



FEATURES / BENEFITS

- 1500 psi rating
- NPT Threads
- Large 6-digit LCD display with two decimal-point precision
- Totalization in pints, quarts, US gallons or liters
- Unit of measure selectable from the front of register
- Resettable and non-resettable totalizer
- Display operation temperature range -4°F to +140°F (-20°C to +60°C)
- Low battery indicator
- Long life field replaceable top load battery
- Accuracy of ± 0.5%
- Calibration factor programmable from front of register
- Calibration factor saved in non-volatile memory



Wichita · Sydney

GREAT PLAINS INDUSTRIES



LM SERIES

ELECTRONIC FLOW METER

DIMENSIONS

Dimension "A"	Dimension "B"	Dimension "C"
4.0 in. (10.2 cm)	3.3 in. (8.4 cm)	3 in. (7.6 cm)

