

HEAVY DUTY MODIFIED SINE WAVE INVERTERS (225/400/800/1000)


CATEGORY:

MODIFIED SINE WAVE
INVERTERS

MODEL RANGE:

GP-225HD
GP-400HD
GP-800HD
GP-1000HD

IDEAL FOR:



GP-225HD



GP-400HD



GP-800HD



GP-1000HD



**1 YEAR
WARRANTY**

GP-225HD / GP-400HD / GP-800HD / GP-1000HD

Run standard AC devices wherever you go. Go Power!'s new Heavy-Duty Modified Sine Wave Inverters bring reliable power to your RV, boat, truck, or even your home if the power goes out.

KEY FEATURES



AC POWER FOR OPTIMAL
PERFORMANCE



EASY TO INSTALL



WIDE VOLTAGE RANGE



USB CONNECTIVITY



FULL OVERLOAD
PROTECTION



HEAVY-DUTY STEEL CASE



CONFORMS TO
UL STD. 458
CERTIFIED TO
CSA STD.
C22.2 No. 107.



P: +1 866 247 6527
E: sales@gopowersolar.com
W: gopowersolar.com

201 - 710 Redbrick St,
Victoria, British Columbia,
Canada, V8T 5J3

SPECIFICATIONS*	GP-225HD	GP-400HD	GP-800HD	GP-1000HD
Continuous Output Power	225 W (VA)	400 W (VA)	800 W (VA)	1000 W (VA)
Maximum Surge Rating	450 W (VA)	800 W (VA)	1600 W (VA)	2000 W (VA)
Output Waveform	Modified Sine Wave			
Output Voltage Range	100 - 120 VAC RMS +5/-15			
Input Voltage	10.5 - 16 VDC			
Efficiency	≥80%	≥80%	≥80%	≥80%
No Load Current Draw	≤0.7 A	≤0.7 A	≤0.8 A	≤0.8 A
USB Output	4.75 - 5.25 VDC / 2.1 A			
Protection	Overload, Over Temperature, Over/Under Voltage, Short Circuit			
Low Battery Alarm ± 0.5 V	10.5 V			
Low Battery Shutdown ± 0.5 V	10 V			
Operating Temperature Range	32°F - 104°F (0°C - 40°C)			
Storage Temperature Range	14°F - 122°F (-10°C - 50°C)			
Cooling	Thermostatically Controlled Fan			
AC Output Connections	2 Standard North American Outlets			
Remote Power Option	No		Yes	
Dimensions (L x W x H)	5.27" x 3.86" x 2.05" (134 mm x 98 mm x 52 mm)	6.30" x 4.25" x 2.64" (160 mm x 108 mm x 66 mm)	7.48" x 4.88" x 2.95" (190 mm x 124 mm x 75 mm)	9.44" x 4.88" x 2.95" (240 mm x 124 mm x 75 mm)
Weight	1.01 lbs (0.46 kg)	1.54 lbs (0.70 kg)	2.31 lbs (1.05 kg)	3.11 lbs (1.41 kg)
Warranty	1 Year			
Inverter Install Kits (sold separately)	Auto Utility Adapter		GP-DC-KIT-2	
Remotes (sold separately)	No Remote Power Option		GP-HD-R	

*Specifications subject to change without notice

PROTECT YOURSELF AND YOUR EQUIPMENT.

FUSE AND CABLE KITS

Go Power! DC installation kits include everything you need to properly connect your Go Power! inverter to the batteries safely. The kit includes 10' large gauge battery cables, tie downs, lugs, and the appropriate inverter fuse (class T fuse) and mounting block.




12 VOLT	INVERTER SIZE
GP-DC-KIT 2	600-1000 W
GP-DC-KIT 3	1100-1800 W
GP-DC-KIT 4	2000-2500 W
GP-DC-KIT 5	2600-3000 W

REMOTELY TURN YOUR INVERTER ON/OFF AND SAVE BATTERY POWER.

INVERTER REMOTE

Remotely power appliances or electronics with the compact Go Power! inverter remote. The remote features an LED indicator showing inverter status, an ON/OFF switch and 25' of cable.



Specifications may be subject to change. Product may not be exactly as shown. Specifications subject to local environmental conditions.



P: +1 866 247 6527
E: sales@gopowersolar.com
W: gopowersolar.com

201 - 710 Redbrick St,
Victoria, British Columbia,
Canada, V8T 5J3