

Go Power!®

DURACUBE



CHARGE YOUR MOBILE DEVICES AND RUN
YOUR ELECTRONICS WITH RELIABLE POWER, ANYWHERE.



DuraCube-500



DuraCube-1000



DuraCube-1500

DURACUBE PORTABLE POWER STATIONS

Reliable Power, Anywhere. Charge your mobile devices and run your electronics wherever your adventure takes you. These portable power stations offer a green, silent source of energy while you enjoy your surroundings.

Available in 500,1000, and 1500 watt-hour sizes, you're sure to find a Go Power! DuraCube that will fit your lifestyle. Ideal for tent camping, camper vans, tent trailers, backyard parties, festivals, fishing, and backup power for emergencies.

FEATURES

- Rugged, lightweight and compact.
- Made with anodized, aircraft grade aluminum for unbeatable quality.
- Equipped with multiple power outlets:
 - 2x AC Outlets
 - 1x USB Type-C
 - 4x USB plugs
 - 1x DC Outlet
- LiFePO4 Lithium battery offers 4x the cycle life of traditional portable packs.
- Built-in MPPT Solar Controller maximizes solar charging.
- Passthrough allows you to power your devices and charge your DuraCUBE simultaneously.
- Built-in Battery Management System (BMS) protects against voltage, current, temperature, and reverse-polarity issues.
- Recharge using solar, (sold separately), DC, or AC adapters



DURACUBE PORTABLE POWER STATION SPECIFICATIONS

SPECIFICATIONS*

DURACUBE-500		DURACUBE-1000		DURACUBE-1500	
General	Operating Temperature	32 °F to 104 °F (0 °C to 40 °C)			
	Dimensions	9.84 x 7.48 x 7.48 in (250 x 190 x 190 mm)	15.16 x 7.48 x 7.48 in (385 x 190 x 190 mm)	18.90 x 7.48 x 7.48 in (480 x 190 x 190 mm)	
	Weight	18.7lb (8.5 kg)	33.lb (15kg)	43.2lb (19.6kg)	
	Simultaneous Charge & Discharge	Yes			
	Car Jump Starter	200A peak to auxiliary jump start up to 2.0T engine 10A continuous charging to jump later (12V only)	N/A		
Battery	Cell Chemistry	LiFePO4			
	Pack Capacity	537.6Wh (42 Ah, 12.8 V)	1036Wh (40.5 Ah, 25.6 V)	1497.6Wh (58.5 Ah, 25.6 V)	
	Cycle Life	Over 2000			
	Storage	Charge every 6 months			
	Protection	Over/under voltage, over current, over temperature			
AC Output	AC Voltage	120 V			
	Frequency	60 Hz			
	AC Waveform	Pure Sine Wave			
	Continuous Output Power	500 W	1000W	1500W	
	Peak Output Power	1000 W 1 second	2000 W 1 second	3000 W 1 second	
	Protection	Overload, over temperature			
	DC Output	USB	4 x USB A: 5V/2.4A 18W max combined power per pair 1 x USB-C: 5V/2.4A, 9V/2A, 12V/1.5A	2 x USB A: 5V/2.4A 12W max combined 2 x USB A: 5V/2.4A, 9V/2A, 12V/1.5A 18W max combined 1 x USB-C: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A 100W max	
DC 12V Barrel Connectors		2 x 12V/5A			
DC 12V Cigarette Port		1x 12V/10A			
Charging	Wall Charging	12-30V, 8A, 120W max	12-30V, 12A, 200W max 12-30V, 12A, 200W max		
	Solar Charging	12-30V, 8A, 120W max			

*Specifications subject to change without notice.

ACCESSORIES INCLUDED



AC Wall Charger



MC4 to DC Adapter



Car Charger Cable