

MPPT SOLAR CONTROLLER PRO R 40/60



CATEGORY:
MPPT CONTROLLERS

MODEL TYPE:
GP-MPPT-PRO-R



**2 YEAR
WARRANTY**

SYSTEM CONTROL AT YOUR FINGERTIPS

Unlock the full potential of your RV's power system with the Go Power! Connect app!

Get real-time insights into your solar charging stats, battery levels, and power consumption on your mobile device. Monitor performance, and set inverter and charging parameters. Available on the iOS and Android app store.



SPECIFICATIONS

System Voltage	12/24V
Battery Voltage Range	9V – 32V
Operating Consumption (Display Backlight ON)	<0.04W
Operating Consumption (Display Backlight OFF)	<0.03W
Communication Mode	TTL
IP Rating	IP32
Display to Controller Port	RJ45
Display to Inverter Port	RJ11
Operating Temperature	14 to 131°F / -10 to 55°C
Humidity	99% N.C.
Dimensions (H x W x D)	4.56 x 4.56 inches (115.82 x 115.82mm)
Weight	1lbs / .5kg
Warranty	2 Years

Use a non-inverting Ethernet cable. GP-MPPT-PRO-R is intended for use with non-inverting Ethernet cables. Use the one provided or be sure to purchase a non-inverting type.

Specifications may be subject to change. Product may not be exactly as shown.
Specifications subject to local environmental conditions.

GP-MPPT-PRO-R

A Solar Controller (or Charge Controller / Regulator) is an essential component of your photovoltaic solar system. The Controller maintains the life of the battery by protecting it from overcharging.

The GP-MPPT-PRO-R is a surface mounted remote display for the GP-MPPT-40-PRO and GP-MPPT-60-PRO charge controllers. The remote shows the charge current to the battery, battery voltage, and battery state of charge (SOC).

KEY FEATURES



**ALLOWS WIRELESS
MONITORING AND CONTROL**



**UP TO 15 METERS
COMMUNICATION DISTANCE**



**SUPPORTS AN EASY-TO-
USE PLUG & PLAY APP**



**EMPLOYS A DEDICATED
BLUETOOTH™ FOR QUICK
COMMUNICATION**



P: +1 866 247 6527
E: sales@gopowersolar.com
W: gopowersolar.com
gopowerfleet.com

201 - 710 Redbrick St,
Victoria, British Columbia,
Canada, V8T 5J3