

BATTERY CHARGER GPC

CATEGORY:

BATTERY CHARGERS

MODEL RANGE:

GPC-35-MAX

GPC-45-MAX

GPC-55-MAX

GPC-75-MAX

GPC-100-MAX



IDEAL FOR:



**2 YEAR
WARRANTY**

GPC

Go Power! Battery Chargers are compact, powerful battery chargers that offer fast, accurate battery charging at a reasonable cost. Go Power! Battery Chargers are reliable, compact and lightweight.

All models feature switchable output modes, one for float charging and one for rapid charging, and a three-stage charger. This is especially useful for batteries which often sit idle for long periods.

KEY FEATURES



**3 STAGE SMART
CHARGING**



13VDC TO 16.5VDC



**FIXED OUTPUT POWER
SUPPLY MODE**



**WORKS WITH ANY
BATTERY TYPE**



**VARIABLE VOLTAGE
ADJUSTMENT**



**INTERNALLY MOUNTED
COOLING FAN**

SYSTEM CONTROL AT YOUR FINGERTIPS

Unlock the full potential of your RV's power system with the Go Power! Connect app!

Get real-time insights into your solar charging stats, battery levels, and power consumption on your mobile device. Monitor performance, and set inverter and charging parameters. Available on the iOS and Android app store.



P: +1 866 247 6527
E: sales@gopowersolar.com
W: gopowersolar.com

201 - 710 Redbrick St,
Victoria, British Columbia,
Canada, V8T 5J3

SPECIFICATIONS*	GPC-35-MAX	GPC-45-MAX	GPC-55-MAX	GPC-75-MAX	GPC-100-MAX
DC Output Voltage (No Load) approx	14.6/13.6/13.2V	14.6/13.6/13.2V	14.6/13.6/13.2V	14.6/13.6/13.2V	14.6/13.6/13.2V
Output Voltage Tolerance (No Load)	+ / - 0.7%	+ / - 0.7%	+ / - 0.7%	+ / - 0.7%	+ / - 0.7%
Output Amperage, Max Continuous	35 amps	45 amps	55 amps	75 amps	100 amps
Output Voltage (Full Load) approx	>13.4V (DC)	>13.4V (DC)	>13.4V (DC)	>13.4V (DC)	>13.4V (DC)
Maximum Power Output, Continuous	510 watts	650 watts	800 watts	1095 watts	1460 watts
Input Voltage Range	105-135AC	105-135AC	105-135AC	105-135AC	105-135AC
Input Voltage Frequency	47-63	47-63	47-63	47-63	47-63
Maximum AC Current @ 108Vac	8 amps	9 amps	11 amps	13 amps	15 amps
Typical Efficiency	>85%	>85%	>85%	>85%	>93%
Max Inrush Current, Single Cycle	40 amps	40 amps	40 amps	40 amps	40 amps
Short Circuit Protection	Yes	Yes	Yes	Yes	Yes
Overload Protection	>100%	>100%	>100%	>100%	>100%
Fan Control	Proportional	Proportional	Proportional	Proportional	Proportional
Thermal Protection	Yes	Yes	Yes	Yes	Yes
Working Temperature Range	0-45C°	0-45C°	0-45C°	0-45C°	0-45C°
Dimensions	7.8 x 9.5 x 3.5"	7.8 x 9.5 x 3.5"	7.8 x 9.5 x 3.5"	7.8 x 9.5 x 3.5"	7.8 x 9.5 x 3.5"
Weight	7.0 lbs	7.0 lbs	7.0 lbs	8.0 lbs	9.0 lbs

Specifications subject to local environmental conditions.
Specifications may be subject to change.



P: +1 866 247 6527
E: sales@gopowersolar.com
W: gopowersolar.com

201 - 710 Redbrick St,
Victoria, British Columbia,
Canada, V8T 5J3