



556 SERIES

Daylight Viewable Panel Mount Indicators

Constant Intensity, 18–48 VDC

MECHANICAL / SPECIFICATIONS

MOUNTING HOLE SIZE:

1.0" (25.4 mm)

MAX PANEL THICKNESS:

0.600" (15.24 mm)

MOUNTING TORQUE: 40 in-lbs

VOLTAGE OPTIONS:

18–48 VDC

(internal resistor included)

OPERATING TEMP:

-30 °C to +85 °C (-22 °F to +185 °F)

STORAGE TEMP:

-40 °C to +100 °C (-40 °F to +212 °F)

ELECTRICAL CONNECTION:

6-32 screw terminals

HOUSING: Brass–

White or Black Nickel Plated

TERMINALS: Brass– Hot solder dip
per Mil-F-14072D, M258, Type II

LENS MATERIAL: Clear UV Stabilized
Polycarbonate (UL 94V-0)

LOCK WASHER: Phosphor Bronze–
White or Black Nickel Plated

NUT: Brass–White or Black Nickel Plated

CERTIFICATIONS & RATINGS

IP66

NEMA 4X


RoHS Compliant w/6C exemption

APPLICATION

The 556 Series LED Panel Mount Indicators incorporate both InGaN and AlInGaP technologies to offer maximum light output. This is a highly durable package, designed to withstand outdoor applications susceptible to rain, dust and sunlight:

- Instrument panels
- Safety applications
- UL 508 panel applications
- Agricultural controls
- Power generators
- Environmental monitoring equipment
- Ground support vehicles
- Pump system controllers
- Transportation - rail, bus, airline
- Lane control
- Display lighting

DIMENSIONS inches [mm]



ORDERING INFORMATION

White Nickel	Black Nickel	Color	Voltage (vdc)	Typ Current (mA)	Typical Intensity (mcd)
556-150A-314F	556-150A-214F	● Red	18–48	7.3–8.2	1470–1500
556-160A-314F	556-160A-214F	● Green		6.5–7.4	200–230
556-170A-314F	556-170A-214F	● Yellow		8.0–8.9	630–660



Dialight reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.dialightsignalsandcomponents.com

Warranty Statement: Except for the warranty expressly provided for at: www.dialight.com/resources/warranties/, Dialight disclaims any and all other warranties, express or implied, including, without limitation, any warranties of merchantability, fitness for a particular purpose, title, and noninfringement.